

Vivid Light B569

Engineered Luxury Vinyl • Style

This product has been discontinued and is no longer part of our regular line.

Product Specifications

Market Segments	Builder, Pro, Residential, Workspace
Sub Category	RCB
Collection	Style
Style Name	Vivid Light
Style Number	B569
Construction	Engineered Luxury Vinyl
Format	Plank
Abrasion Resistance	General Commercial Use
Material	Recycled PVC DOP Free
Core Material	70% Recycled & Virgin PVC / 30 % Mineral
Width	8.03" (204 mm)
Total Thickness	0.197" (5 mm)
Wear Layer Thickness	0.0220" (0.5500 mm)
Core Thickness	n/a
Backing	None
Edges	4-Sided Micro Bevel
Locking System	DreamClick
Backing Thickness	n/a
Finish	Registered Embossed
Top Surface	UV-Cured Polyurethane
Gloss	Matte
Pattern Repeat	8
IIC	n/a
STC	n/a
Design	Wood
Formaldehyde	E1
Vinyl Thickness	n/a
Length	52.2" (1326 mm)
Certifications	FloorScore, E1 Certified, Phthalates-Free, BLC Certification, QuickShip, Virgin PVC
Installation Methods	Floating, Compatible with embedded radiant heating, Multidirectional 🔗 Engineered Luxury Vinyl Installation Guide - Style 🔗 Engineered Luxury Vinyl Installation Video - DreamClick Locking System

Vivid Light B569

Engineered Luxury Vinyl • Style

Plank Packaging information

Units Per Box	8
Boxes Per Pallet	56
Box Weight	33.07 pounds (15001.10 grams)
Square Meters Per Box	2.16
Square Meters Per Pallet	121.17
Square Feet Per Box	23.29
Square Feet Per Pallet	1304.24

Warranties

- [Engineered Luxury Vinyl Warranty Guide](#)
- [Engineered Luxury Vinyl Maintenance Guide](#)

Residential use	No Questions Asked Replacement <i>30 days</i> Waterproof <i>Lifetime</i> Petproof <i>Lifetime</i> Wear <i>Lifetime</i> Manufacturing Defects <i>Lifetime</i> Stain Resistance <i>Lifetime</i> Fade <i>Lifetime</i>
Commercial use	Manufacturing Defects <i>15 Years</i> Fade <i>15 Years</i> Waterproof <i>Lifetime</i> Petproof <i>Lifetime</i> Wear <i>15 Years</i> Stain Resistance <i>15 Years</i>

Vivid Light B569

Engineered Luxury Vinyl • Style

Physical Properties

Test	Test method	Result
Stain resistance	EN ISO 1815	Yes
Sound reduction: impact sound	EN ISO 717/2	11 dB
Slip resistance	DIN 51130	R10
Reflected walking sound	EN ISO 16205	54.4 dB
Castor chair resistance	EN ISO 4918	Pass

Chemical Composition

Test	Test method	Result
Formaldehyde Emission	EN ISO 717-1	E1

Technical Information

Test	Test method	Result
Fire resistance	EN ISO 13501-1	Bfl-s1
Underfloor heating	EN ISO 12524	Suitable max 27°C (80°F) / Electrical floorheating systems max 60 W/m ²
RRL pendulum test: dry	CEN/TS 15676	66.5
Residual indentation	EN ISO 24343-1	< 0.10 mm
Thermal resistance	EN ISO 8302	0.0293 m ² K/W
Chemical resistance	EN ISO 26987	OK
RRL pendulum test: wet	CEN/TS 15676	59.7
Dimensional stability	EN ISO 23999	≤ 0,05 %
Fastness to light	EN ISO 105 B02	>6

Vivid Light B569

Engineered Luxury Vinyl • Style

Styles offered



#B367 (Plank)
Cracked Dark Brown
Registered Embossed
Dropped Product



#B560 (Plank)
Elegant Light Grey
Registered Embossed
Dropped Product



#B561 (Plank)
Elegant Light Greige
Registered Embossed
Dropped Product



#B562 (Plank)
Elegant Natural
Registered Embossed
Dropped Product




#B563 (Plank)
Elegant Natural Brown
Registered Embossed
Dropped Product



#B564 (Plank)
Elegant Medium Grey
Registered Embossed
Dropped Product




#B565 (Plank)
Elegant Dark Grey
Registered Embossed
Dropped Product



#B567 (Plank)
Cracked Natural Brown
Registered Embossed
Dropped Product



#b569 (Plank)
Vivid Light
Registered Embossed
Dropped Product



#B571 (Plank)
Vivid Natural Brown
Registered Embossed
Dropped Product



#B574 (Plank)
Rustic Light
Registered Embossed
Dropped Product