

Vision T34V

Carpet Tiles • Modulyss

Product Specifications

Market Segments	Hospitality, Pro, Workspace
Brand	Modulyss
Collection	Modulyss
Style Name	Vision
Style Number	T34V
Colors	13
Construction	Tufted Loop
Format	Tile
Fiber Type	100% BCF Solution Dyed Nylon
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	20.06 oz./y ² (680.0 g/m ²)
Pile Height	5/32 in (3.7 mm)
Total Height	5/16 in (7.7 mm)
Backing	Back2Back Modified Bitumen
Stitch Count	0 /in (0 /10 cm)
Gauge	1/12 in (2.11 mm)
Density Factor	4956
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70 & C.G.S.B. 4-GP-129
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	n/a
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, Certified A+, GUT-NR
Installation Methods	Quarter Turn, Monolithic, Brick
	🔗 Modulyss Carpet Tiles Installation Guide

Vision T34V

Carpet Tiles • Modulyss

Tile Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	50.71 Pounds (23001.83 Grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99

Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Wear Resistance <i>15 Years</i>
	Edge Ravelling <i>15 Years</i>
	Delamination Resistance <i>15 Years</i>
	Dimensional Stability <i>15 Years</i>
	Anti-Zippering <i>15 Years</i>
	Colorfastness <i>15 Years</i>
	Manufacturing Defects <i>15 Years</i>
	Stain Resistance <i>15 Years</i>
	Static Control <i>15 Years</i>

Vision T34V

Carpet Tiles • Modulyss

Technical Information

Test

Impact noise rating
Fire resistance
Colorfastness to water
Rubbing fastness
Castor chair resistance
Permanent antistatic
Sound absorption
Thermal resistance
Dimensional stability
Transversal resistance
Fastness to light

Test method

ISO 10140
ASTM E648
EN ISO 105-E01
EN ISO 105-X12
EN 985
ISO 6356
ISO 354
ISO 8302
EN 986
ISO / DIS 10965
EN ISO 105 B02

Result

ΔL_w : 25 dB
Class 1
 ≥ 4
 ≥ 4
A: continuous use
 ≤ 2 kV
125 Hz: a_s 0.03 | 250 Hz:
 a_s 0.00 | 500 Hz: a_s 0.10 |
1000 Hz: a_s 0.19 | 2000
Hz: a_s 0.36 | 4000 Hz: a_s
0.42
0.091 m² K/W
max 0.20%
 $\leq 1 \times 10^9$ Ohm
 ≥ 7

Certifications

Test

Classification

Test method

EN 1307


Result

33-LC2

Vision T34V

Carpet Tiles • Modulyss

Styles offered



#t34v (Tile)
Vision