

# Quadra TQUD

## Carpet Tiles • Mainstreet Tiles - Nyluxe

### Product Specifications

<b>Market Segments</b>	Builder, Hospitality, Pro, Property Management, Residential, Senior Living, Workspace
<b>Brand</b>	Nyluxe Tiles
<b>Collection</b>	Mainstreet Tiles - Nyluxe
<b>Style Name</b>	Quadra
<b>Style Number</b>	TQUD
<b>Colors</b>	6
<b>Construction</b>	Multi-Level Loop
<b>Format</b>	Tile
<b>Fiber Type</b>	100% Nylon 6
<b>Abrasion Resistance</b>	General Commercial Use
<b>Dye Method</b>	Solution Dyed
<b>Pile Weight</b>	20.00 oz./y <sup>2</sup> (678.1 g/m <sup>2</sup> )
<b>Pile Height</b>	1/8 in (3.0 mm)
<b>Total Height</b>	1/4 in (6.0 mm)
<b>Backing</b>	Endurobac
<b>Stitch Count</b>	14/in (55/10 cm)
<b>Gauge</b>	1/10 in (2.54 mm)
<b>Density Factor</b>	5891
<b>Static Control</b>	n/a
<b>Flammability</b>	Meets DOC FF-1-70
<b>Flooring Radiant Panel</b>	Class 1 (ASTM E-648)
<b>Tarr</b>	0
<b>Indoor Air Quality</b>	GLP 3325
<b>Dimension</b>	19.7 x 19.7" (50 X 50 cm)
<b>Color Fastness</b>	Meets 5.0 AATCC 16
<b>Certifications</b>	Green Label Plus, QuickShip, SoilScreen, Stain Control
<b>Installation Methods</b>	Quarter Turn, Brick <a href="#">🔗 Carpet Tiles Installation Guide</a>

# Quadra TQUD

## Carpet Tiles • Mainstreet Tiles - Nyluxe

### Tile Packaging information

Units Per Box	20
Boxes Per Pallet	28
Box Weight	51.55 pounds (23381.58 grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	167.44
Square Meters Per Pallet	139.98

### Warranties

[🔗 Carpet Tiles Warranty Guide](#)

[🔗 Carpet Tiles Commercial Care and Maintenance Guide](#)

#### Residential use

Static Control *Lifetime*  
Wear Resistance *Lifetime*  
Edge Ravelling *Lifetime*  
Delamination Resistance *Lifetime*  
Dimensional Stability *Lifetime*  
Anti-Zippering *Lifetime*  
No Questions Asked Replacement *30 days*  
Stain Resistance *Lifetime*

#### Commercial use

Static Control *15 Years*  
Stain Resistance *15 Years*  
Wear Resistance *15 Years*  
Edge Ravelling *15 Years*  
Delamination Resistance *15 Years*  
Dimensional Stability *15 Years*  
Anti-Zippering *15 Years*

# Quadra TQUD

## Carpet Tiles • Mainstreet Tiles - Nyluxe


### Performance

Test	Test method	Result
Color Fastness	AATCC/16	5/5 on Grey Scale
Flammability	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
Dimensional Stability	EN 986	< 0.20%
Impact Sound Insulation	ISO 140-8	$\Delta L_w$ 23 dB
Static Propensity	ISO 6356	0.2 kV
Critical Radiant Flux	ASTM E648-08	Class 1
VOC Emission	ASTM D5116-06	< 0.5 mg/m <sup>2</sup> / hour (CRI GLP)
Smoke Density	EN ISO 9239-1: 2002	< 450
Castor Chair Resistance	DIN 54324	R $\geq$ 2.4
Sound Absorption Level	EN ISO 11654	$\alpha_w$ : 0.15 (H)
Thermal Resistance	ISO 8302	0.04 m <sup>2</sup> K/W
Soiling Propensity	ASTM D 6540-00	4


# Quadra TQUD

Carpet Tiles • Mainstreet Tiles - Nyluxe


## Styles offered




#TALL (Tile)  
Allure




#TANG (Tile)  
Angula  
Limited Stock




#TAPP (Tile)  
Appeal




#TDIV (Tile)  
Diversion



#TDYN (Tile)  
Dynamo  
Limited Stock




#TEVO (Tile)  
Evolio




#TFAS (Tile)  
Fascination




#TKIN (Tile)  
Kinematic  
Dropped Product



#TMAG (Tile)  
Magnetism




#TNEX (Tile)  
Nexio



#TPIC (Tile)  
Pictora  
Dropped Product



#TQUA (Tile)  
Quantum




#tqud (Tile)  
Quadra



#TREL (Tile)  
Relativity  
Limited Stock



#TSYM (Tile)  
Symbio



#TTEC (Tile)  
Tectonic

## Accessories



**301 Carpet Tiles Adhesive - 4 U.S. Gallons**

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m<sup>2</sup> / 15 L)

Non-Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m<sup>2</sup> / 15 L)

[↗ Specifications - 301 Pressure Sensitive Carpet Tile Adhesive](#)

[↗ Label - 301 Pressure Sensitive Carpet Tile Adhesive](#)

[↗ SDS - 301 Pressure Sensitive Carpet Tile Adhesive](#)

 **beaulieu**  
www.beulieucanada.com

Technical Bulletin

page 4 of 4