

Opposite T39

Carpet Tiles • Modulyss

Product Specifications

Market Segments	Hospitality, Pro, Workspace
Brand	Modulyss
Collection	Modulyss
Style Name	Opposite
Style Number	T39
Colors	11
Construction	Minituft Loop
Format	Tile
Fiber Type	100% BCF Solution Dyed Nylon
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	14.75 oz./y ² (500.0 g/m ²)
Pile Height	3/64 in (1.1 mm)
Total Height	15/64 in (5.9 mm)
Backing	Back2Back Modified Bitumen
Stitch Count	0/in (0/10 cm)
Gauge	5/64 in (1.98 mm)
Density Factor	12259
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70 & C.G.S.B. 4-GP-129
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	n/a
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, Certified A+, GUT-NR
Installation Methods	Quarter Turn

[!\[\]\(666e09182d4cd268646ea700ea60dcdf_img.jpg\) **Modulyss Carpet Tiles Installation Guide**](#)

Opposite T39

Carpet Tiles • Modulyss

Tile Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	50.71 pounds (23001.83 grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99

Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Anti-Zippering <i>15 Years</i>
	Colorfastness <i>15 Years</i>
	Manufacturing Defects <i>15 Years</i>
	Stain Resistance <i>15 Years</i>
	Static Control <i>15 Years</i>
	Wear Resistance <i>15 Years</i>
	Delamination Resistance <i>15 Years</i>
	Edge Ravelling <i>15 Years</i>
	Dimensional Stability <i>15 Years</i>

Opposite T39

Carpet Tiles • Modulyss

Technical Information

Test

Impact noise rating
Fire resistance
Colorfastness to water
Rubbing fastness
Castor chair resistance
Permanent antistatic
Sound absorption
Thermal resistance
Dimensional stability
Transversal resistance
Fastness to light

Test method

ISO 10140
ASTM E648
EN ISO 105-E01
EN ISO 105-X12
EN 985
ISO 6356
ISO 354
ISO 8302
EN 986
ISO / DIS 10965
EN ISO 105 B02

Result

ΔL_w 16 dB
Class 1
 ≥ 4
 ≥ 4
A: continuous use
 ≤ 2 kV
125 Hz: a_s 0.00 | 250 Hz:
 a_s 0.02 | 500 Hz: a_s 0.05 |
1000 Hz: a_s 0.12 | 2000
Hz: a_s 0.24 | 4000 Hz: a_s
0.27
0.048 m² K/W
max 0.20%
 $\leq 10^9$ Ohm
 ≥ 7

Certifications

Test

Classification

Test method

EN 1307


Result

33-LC1


Opposite T39

Carpet Tiles • Modulyss

Styles offered



#T34M (Tile)
Motion



#T34V (Tile)
Vision



#t39 (Tile)
Opposite
Dropped Product



#TQS1 (Tile)
Alpha
Dropped Product



#TQS2 (Tile)
Frame



#TQS3 (Tile)
Wall
Dropped Product