

Grind T47

Carpet Tiles • Modulyss - Handcraft

Product Specifications

Market Segments	Hospitality, Pro, Workspace
Brand	Modulyss
Collection	Modulyss - Handcraft
Style Name	Grind
Style Number	T47
Colors	7
Construction	Minituft Loop
Format	Tile
Fiber Type	100% Econyl® Sol. Dyed Recycled Nylon
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	17.70 oz./y ² (600.0 g/m ²)
Pile Height	3/64 in (1.0 mm)
Total Height	7/32 in (5.5 mm)
Backing	Ecoback
Stitch Count	0 /in (0 /10 cm)
Gauge	5/64 in (1.98 mm)
Density Factor	16181
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70 & C.G.S.B. 4-GP-129
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	n/a
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, Certified CE, GUT-NR, Cradle to Cradle Certified™ Gold - Color 130, Cradle to Cradle Certified™ Silver - Colors 586,6
Installation Methods	Ashlar, Quarter Turn, Brick
	🔗 Modulyss Carpet Tiles Installation Guide

Grind T47

Carpet Tiles • Modulyss - Handcraft

Tile Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	49.63 Pounds (22513.59 Grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99

Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Wear Resistance <i>15 Years</i>
	Static Control <i>15 Years</i>
	Stain Resistance <i>15 Years</i>
	Manufacturing Defects <i>15 Years</i>
	Colorfastness <i>15 Years</i>
	Edge Ravelling <i>15 Years</i>
	Anti-Zippering <i>15 Years</i>
	Dimensional Stability <i>15 Years</i>
	Delamination Resistance <i>15 Years</i>

Grind T47

Carpet Tiles • Modulyss - Handcraft

Technical Information

Test

Impact noise rating
Fire resistance
Colorfastness to water
Rubbing fastness
Castor chair resistance
Permanent antistatic
Sound absorption
Thermal resistance
Dimensional stability
Transversal resistance
Fastness to light

Test method

ISO 10140
EN 13501-1
EN ISO 105-E01
EN ISO 105-X12
EN 985
ISO 6356
ISO 354
ISO 8302
EN 986
ISO / DIS 10965
ISO 105-B02

Result

ΔL_w 15 dB
Cfl-s1
 ≥ 4
 ≥ 4
A: continuous use
 ≤ 2 kV
125 Hz: a_s 0.02 | 250 Hz:
 a_s 0.00 | 500 Hz: a_s 0.04 |
1000 Hz: a_s 0.12 | 2000
Hz: a_s 0.23 | 4000 Hz: a_s
0.23
0.042 m² K/W
Max 0.2 %
 $\leq 1 \times 10^9$ Ohm
 ≥ 7

Certifications

Test

Classification

Test method

EN 1307

Result

33-LC1

Grind T47

Carpet Tiles • Modulyss - Handcraft

Styles offered



#t47 (Tile)
Grind