

Gyant Warm Natural B2501

Laminate • Ocean+

Product Specifications

Market Segments	Builder, Hospitality, Pro, Residential, Senior Living
Sub Category	Water-Resistant
Collection	Ocean+
Style Name	Gyant Warm Natural
Style Number	B2501
Construction	Laminate
Format	Plank
Abrasion Resistance	AC5 Class 33: Heavy Commercial Use
Species	Oak
Width	7.48" (190 mm)
Total Thickness	0.472" (12 mm)
Core Thickness	n/a
Backing	n/a
Edges	4-Sided Micro Bevel with Water Repellant Coating
Locking System	Pentaloc Drop Lock
Attached Backing	No
Backing Thickness	None
Finish	Registered Embossed
Top Surface	Aluminum Oxide
Gloss	Matte
Pattern Repeat	10
IIC	n/a
STC	n/a
Formaldehyde	E1
Length	50.708" (1288 mm)
Certifications	FloorScore, E1 Certified, BLC Certification, QuickShip, TSCA Title VI Compliant
Installation Methods	Floating, Compatible with embedded radiant heating 🔗 Laminate Installation Guide (Pentaloc Drop Lock) 🔗 Berry Alloc Laminate Installation Video - Pentaloc Drop Lock

Gyant Warm Natural B2501

Laminate • Ocean+

Plank Packaging information

Units Per Box	6
Boxes Per Pallet	56
Box Weight	35.23 pounds (15981.86 grams)
Square Meters Per Box	1.47
Square Meters Per Pallet	82.20
Square Feet Per Box	15.8
Square Feet Per Pallet	884.8

Warranties

- [Berry Alloc Laminate Warranty Guide](#)
- [Berry Alloc Laminate Maintenance Guide](#)

Residential use	No Questions Asked Replacement <i>30 days</i> Manufacturing Defects <i>Lifetime</i> Stain <i>Lifetime</i> Wear <i>Lifetime</i> Fade <i>Lifetime</i>
Commercial use	Stain <i>10 Years</i> Fade <i>10 Years</i> Wear <i>10 Years</i> Manufacturing Defects <i>10 Years</i>

Moldings



Reducer
Coordinating
94" X 0.615" X 2.0"
(2388 mm X 15.621 mm X 50.80 mm)



Stair Nose Mdf
Coordinating
94" X 0.93" X 2.1"
(2388 mm X 23.622 mm X 53.34 mm)



T-Molding
Coordinating
94" X 0.62" X 1.750"
(2388 mm X 15.748 mm X 44.45 mm)

Gyant Warm Natural B2501

Laminate • Ocean+

Physical Properties

Test	Test method	Result
Stain resistance	EN 438	5 (groups 1+2); 4 (group 3)
Reaction to fire classification	EN 13501-1	Cfl-s1
Slip resistance	EN 13893	Class DS
Water resistance	ISO 4760	up to 24 hours
Impact resistance	EN 13329	small ball: ≥ 70 mm - big ball: ≥ 1000 mm
Abrasion resistance	EN 13329	AC5 (IP ≥6000)
Castor chair resistance	EN 425	No damage with type W wheels
Core density	EN 323	900 kg/m ³
Thickness Swelling	ISO 24336	12% (requirement ≤ 15%)
Effect of furniture leg	EN 16581	No damage (foot type 0)


Chemical Composition

Test	Test method	Result
Formaldehyde Emission	EN 717-1	E1


Gyant Warm Natural B2501

Laminate • Ocean+


Styles offered



#b2501 (Plank)
Gyant Warm Natural
Registered Embossed



#B2502 (Plank)
Gyant Warm Brown
Registered Embossed



#B2505 (Plank)
Select Sand Natural
Registered Embossed



#B2506 (Plank)
Select Light Brown
Registered Embossed



#B3041 (Plank)
Epic Light
Registered Embossed



#B3042 (Plank)
Epic Natural
Registered Embossed