

Chicago 2110

Luxury Vinyl • Skyline

Product Specifications

Market Segments	Hospitality, Pro, Residential, Workspace
Brand	PermaLuxe
Sub Category	LVT
Collection	Skyline
Style Name	Chicago
Style Number	2110
Construction	Luxury Vinyl
Format	Tile
Abrasion Resistance	General Commercial Use
Material	Virgin PVC
Width	12" (304.8 mm)
Total Thickness	0.118" (3 mm)
Wear Layer Thickness	0.0220" (0.5500 mm)
Interlayer	None
Backing	Dry Back
Edges	4-Sided Micro Bevel
Locking System	None
Finish	Travertine
Top Surface	UV-Cured Polyurethane & Ceramic Bead Technology
Gloss	Matte
Pattern Repeat	6
IIC	62
STC	68
Design	Concrete
Formaldehyde	E1
Length	24" (609.6 mm)
Certifications	QuickShip, Virgin PVC, FloorScore, E1 Certified, Phthalates Free, BLC Certification
Installation Methods	Compatible with embedded radiant heating, Glued
	🔗 Luxury Vinyl Installation Guide (DryBack)
	🔗 Wall Installation Guide - Luxury Vinyl

Chicago 2110

Luxury Vinyl • Skyline

Tile Packaging information

Units Per Box	18
Boxes Per Pallet	56
Box Weight	39.60 Pounds (17962.24 Grams)
Square Meters Per Box	3.34
Square Meters Per Pallet	187.29
Square Feet Per Box	36
Square Feet Per Pallet	2016

Warranties

- [Luxury Vinyl Warranty Guide](#)
- [Luxury Vinyl Care & Maintenance Guide](#)


Residential use

- Wear *Lifetime*
- Stain *Lifetime*
- Manufacturing Defects *Lifetime*
- Fade *Lifetime*
- No Questions Asked Replacement *30 days*
- Waterproof *Lifetime*
- Petproof *Lifetime*

Commercial use

- Manufacturing Defects *15 Years*
- Wear *15 Years*
- Stain *15 Years*
- Fade *15 Years*
- Waterproof *Lifetime*
- Petproof *Lifetime*

Moldings



Multitrim

Coordinating
94" X 0.23" X 1.593"
(2350 mm X 5.842 mm X 40.481 mm)

PVC Stair Nose

Coordinating
94" X 1.16" X 2"
(2350 mm X 25.4 mm X 50.80 mm)

Chicago 2110

Luxury Vinyl • Skyline

Dimensional Tolerance

Test

Height difference
Curling in the presence of heat
Squareness
Width tolerance
Gaps between planks
Dimensional stability
Length tolerance
Thickness tolerance

Test method

Max 0.15 mm
EN ISO 23999 (≤ 2 mm)
Max 0.25 mm
ASTM F2055 0.4 mm / 305 mm
Max 0.15 mm
ASTM F2199-09 (max 1.67 mm per m)
ASTM F2055 0.4 mm / 305 mm
ASTM F386 0.13 mm

Result

Pass
Pass
Pass
Pass
Pass
Pass
Pass
Pass

Physical Properties

Test

Residual indentation
Surface scratch resistance
Reaction to fire classification
Static load limit
Airborne sound transmission (STC)
Density
Peel resistance
Flexibility
Impact sound transmission (IIC)
Slip resistance
Smoke density
Color stability to heat exposure
Abrasion resistance
Resistance to chemicals
Critical radiant flux class
Castor chair resistance

Test method

ASTM F1914-07 (average max 8%)
ISO 1518-1: 2011 (≥ 2500 g)
EN 13501-1: 2007
ASTM F970
ASTM E90 (2009) ASTM E413 (2010)
ISO 1183-1: 2012 (± 0.05 g/cm³)
EN ISO 24345 - Min 50 N / 50 mm
ASTM F137-08 and ASTM F1700-04
ASTM E492-09 (2016) ASTM E989-06 (2012)
EN 14041 and EN 13893
ASTM E662
ASTM F1514-03 (max $\Delta E=8$)
EN 660-2-1999 Range between 0.010 g-0.060 g /1000
ASTM F925-13 (max slight change)
EN ISO 9239-1
EN 425: 2002

Result

Pass
 ≥ 3200 g
Bfl-s1
 ≥ 1000 PSI
68
1.8-2.0 g/cm³
Pass
Pass
62
Class DS
Pass
Pass
Pass
Pass
Bfl
Pass

Chemical Composition

Test

Phthalates
Antibacterial wear layer
TVOC (Total Volatile Organic Compounds)
Formaldehyde Emission
Indoor air quality

Test method

Prop 65
ASTM E2180-07
CDPH /EHLB Standard Method V1.1
EN 717-1: 2004
SCS-EC10.3-2014 v3.0

Result

None detected
99.9% Reduction
Pass
E1
FloorScore Certified

Chicago 2110

Luxury Vinyl • Skyline

Styles offered



#2110 (Tile)

Chicago

Travertine

Accessories



701 Luxury Vinyl Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Non-Porous: 1/16" x 1/32" x 1/32" V-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

Non-Porous Coverage

1,000 to 1,200 sq.ft. / 4 U.S. Gallons (93 to 112 m² / 15 L)

[!\[\]\(899d8b7697d64725bf017d3296cfcf1b_img.jpg\) Label - 701 Vinyl Flooring Adhesive](#)

[!\[\]\(c1168d6a8b365d11e842ece304635fa7_img.jpg\) SDS - 701 Vinyl Flooring Adhesive](#)

[!\[\]\(cbd8541a32dfc32f356f5c6c994b0a21_img.jpg\) Specifications - 701 Vinyl Flooring Adhesive](#)