

First Straightline T25

Carpet Tiles • Modulyss - First

Product Specifications

Market Segments	Builder, Hospitality, Pro, Property Management, Senior Living, Workspace
Brand	Modulyss
Collection	Modulyss - First
Style Name	First Straightline
Style Number	T25
Colors	22
Construction	Tufted Loop
Format	Tile
Fiber Type	100% Solution Dyed Nylon 6
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	15.93 oz./y ² (540.0 g/m ²)
Pile Height	1/8 in (2.9 mm)
Total Height	1/4 in (6.2 mm)
Backing	Back2Back Modified Bitumen
Stitch Count	0/in (0/10 cm)
Gauge	1/10 in (2.54 mm)
Density Factor	5022
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	n/a
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	n/a
Certifications	Green Label Plus, Certified A+, Certified CE, GUT-NR
Installation Methods	Quarter Turn, Monolithic, Brick
	🔗 Modulyss Carpet Tiles Installation Guide

First Straightline T25

Carpet Tiles • Modulyss - First

Tile Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	47.42 pounds (21509.97 grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99

Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Colorfastness <i>15 Years</i>
	Anti-Zippering <i>15 Years</i>
	Dimensional Stability <i>15 Years</i>
	Delamination Resistance <i>15 Years</i>
	Edge Ravelling <i>15 Years</i>
	Wear Resistance <i>15 Years</i>
	Static Control <i>15 Years</i>
	Stain Resistance <i>15 Years</i>
	Manufacturing Defects <i>15 Years</i>

First Straightline T25

Carpet Tiles • Modulyss - First

Technical Information

Test

Impact noise rating
Fire resistance
Colorfastness to water
Rubbing fastness
Castor chair resistance
Permanent antistatic
Sound absorption
Thermal resistance
Dimensional stability
Transversal resistance
Fastness to light

Test method

ISO 10140
EN 13501-1
EN ISO 105-E01
EN ISO 105-X12
EN 985
ISO 6356
ISO 354
ISO 8302
EN 986
ISO / DIS 10965
ISO 105-B02

Result

ΔL_w : ca 26 dB
Bfl-s1
 ≥ 4
 ≥ 4
A: continuous use
 ≤ 2 kV
 α_w : 0,15
0.062 m²K/W
Max 0.2 %
 $\leq 1 \times 10^9$ Ohm
 ≥ 7

Certifications

Test

Classification

Test method

EN 1307

Result

33-LC1

First Straightline T25

Carpet Tiles • Modulyss - First

Styles offered



#T24 (Tile)
First Forward



#T24S (Tile)
First Forward-Stk




#t25 (Tile)
First Straightline



#T26 (Tile)
First Streamline



#T26S (Tile)
First Streamline-Stk
Dropped Product



#T27 (Tile)
First Decode



#T27S (Tile)
First Decode-Stk



#T28 (Tile)
First Define



#T28S (Tile)
First Define-Stk
Dropped Product