Benefits

Safe and healthy Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the

market

Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their

circulation Slip Resistant

Cushion falls and reduces the risk of injury

Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to

muscles and articulations

Environmentally-Friendly Made with solution-dyed fibers a process that reduces significantly water consumption

Best-in-class Warranty 30 Days No Questions Asked Replacement

Limitless designabilities One of the most versatile floor coverings because you get to choose from a wide range of colors and textures

Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable Without a doubt, the most comfortable flooring

Greatest soundproofing and insulating properties

Reduces heat loss

Soft and warm to the touch

Quickship Stock product for faster delivery

Stain resistant & easy to clean Protected with Stain Control for resistance to the most stubborn stains

Treated with SoilScreen to keep soil on the surface making your carpet easier to clean

High performance Made with our Nyluxe solution-dyed nylon fiber for outstanding wear resistance

Part of our Mainstreet Nyluxe product offering, ideal for general commercial applications

Made with EnduroBac backing which provides strong and non-fraying edge and offers durability and

exceptional dimensional stability

Easy to install and repair Easy installation with our 301 Carpet Tiles Adhesive

Modular floor covering for fast and easy repair when needed

Single Bulletin page 1 of 4

Product Specifications

Brand

Market Segments Builder, Hospitality, Pro, Property

Management, Residential, Senior

Living, Workspace Nyluxe Tiles

Collection Mainstreet Tiles - Nyluxe

Style Name Quadra Style Number **TQUD** Colors

Construction Multi-Level Loop

Format

Fiber Type 100% Solution Dyed Nylon 6 Abrasion Resistance General Commercial Use

Dye Method Solution Dyed

Pile Weight 20.00 oz./y² (678.1 g/m²)

Pile Height 1/8 in (3.0 mm) **Total Height** 1/4 in (6.0 mm) Backing Endurobac Stitch Count 14 /in (55 /10 cm) Gauge 1/10 in (2.54 mm)

Density Factor 5891 Static Control

Flammability Meets DOC FF-1-70 Flooring Radiant Panel Class 1 (ASTM E-648)

Tarr


Indoor Air Quality GLP 3325

Dimension 19.7 x 19.7" (50 X 50 cm) Color Fastness Meets 5.0 AATCC 16 Certifications Green Label Plus, QuickShip, SoilScreen, Stain Control

Quarter Turn, Brick

Installation Methods

☑ Carpet Tiles Installation Guide



Color Names & Numbers

#T549 Sweet Brownies #T544 Sahara Taupe #T547 Mysterious Taupe #T574 Foggy Horizon #T577 Dark Shadow #T578 Wired Black

Warranties

Carpet Tiles Warranty Guide

☑ Carpet Tiles Commercial Care and Maintenance Guide

Residential use Stain Resistance Lifetime

> Static Control Lifetime Wear Resistance Lifetime Edge Ravelling Lifetime Delamination Resistance

Lifetime

Anti-Zippering Lifetime Dimensional Stability Lifetime

No Questions Asked Replacement 30 days

Commercial use Edge Ravelling 15 Years

> Wear Resistance 15 Years Static Control 15 Years Stain Resistance 15 Years Anti-Zippering 15 Years Dimensional Stability 15 Years Delamination Resistance 15

> > page 2 of 4

Years



Colors














Sweet Brownies

#T544 Sahara Taupe

#1547 Mysterious Taupe

Foggy Horizon

Dark Shadow

#1578 Wired Black

Packaging information

Units Per Box 20 Boxes Per Pallet 28

Box Weight 51.55 Pounds (23381.58 Grams)

Square Yards Per Box5.98Square Meters Per Box5.00Square Yards Per Pallet167.44Square Meters Per Pallet139.98

Single Bulletin page 3 of 4

Accessories



301 Carpet Tiles Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres) 1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

 $680 - 760 \text{ sq.ft.} / 4 \text{ Gallons } (63 - 71 \text{ m}^2 / 15 \text{ L})$

Non-Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m^2 / 15 L)

- ☑ SDS 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Specifications 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Label 301 Pressure Sensitive Carpet Tile Adhesive



Single Bulletin page 4 of 4