Benefits

Safe and healthy Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the

market

Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their

circulation Slip Resistant

Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to

muscles and articulations

Environmentally-FriendlyMade with solution-dyed fibers a process that reduces significantly water consumption

Best-in-class Warranty 30 Days No Questions Asked Replacement

Limitless designabilities One of the most versatile floor coverings because you get to choose from a wide range of colors and textures

Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable Without a doubt, the most comfortable flooring

Greatest soundproofing and insulating properties

Reduces heat loss

Soft and warm to the touch

Quickship Stock product for faster delivery

Stain resistant & easy to clean Protected with Stain Control for resistance to the most stubborn stains

Treated with SoilScreen to keep soil on the surface making your carpet easier to clean

High performance Made with our Nyluxe solution-dyed nylon fiber for outstanding wear resistance

Part of our Mainstreet Nyluxe product offering, ideal for general commercial applications

Easy to install and repair Easy installation with our 301 Carpet Tiles Adhesive

Modular floor covering for fast and easy repair when needed



Single Bulletin page 1 of 4

Product Specifications

Market Segments Builder, Hospitality, Pro, Property

Management, Residential, Senior

Living, Workspace Nyluxe Tiles

Collection Mainstreet Tiles - Nyluxe

Style NameSymbioStyle NumberTSYMColors6

Brand

Construction Multi-Level Loop

Format Til

Fiber Type 100% Solution Dyed Nylon Abrasion Resistance General Commercial Use

Dye Method Solution Dyed

 Pile Weight
 16.02 oz./y² (543.0 g/m²)

 Pile Height
 9/64 in (3.5 mm)

 Total Height
 0 in (0.0 mm)

 Backing
 Eco3Rbac

 Stitch Count
 12 /in (47 /10 cm)

 Gauge
 1/10 in (2.54 mm)

Density Factor 5852

Static Control Less Than 2.0 kV (AATCC 134)

Flammability Meets DOC FF-1-70
Flooring Radiant Panel Class 1 (ASTM E-648)

Tarr

Installation Methods

Indoor Air Quality GLP 101162

Dimension19.7 x 19.7" (50 X 50 cm)Color FastnessMeets 5.0 AATCC 16CertificationsGreen Label Plus, QuickShip,
Environmental Product Declaration

(EPD), SoilScreen, Stain Control Quarter Turn, Monolithic, Brick

☑ Carpet Tiles Installation Guide



Color Names & Numbers

#01	Heavy Steel	#02	Mixed Pebbles
#03	Wild Storm	#04	Noble Owl
#05	Smoky Green	#06	Dried Oregano

Warranties

Carpet Tiles Warranty Guide

☑ Carpet Tiles Care & Maintenance Guide

Residential use Stain Resistance Lifetime

Static Control *Lifetime*Wear Resistance *Lifetime*Edge Ravelling *Lifetime*Delamination Resistance

Lifetime

Anti-Zippering Lifetime No Questions Asked Replacement 30 days Colorfastness Lifetime

Commercial use Edge Ravelling 15 Years

Wear Resistance 15 Years
Static Control 15 Years
Stain Resistance 15 Years
Colorfastness 15 Years
Anti-Zippering 15 Years
Delamination Resistance 15

page 2 of 4

Years



Colors













Mixed Pebbles Heavy Steel

Noble Owl

Smoky Green

Dried Oregano

Packaging information

Units Per Box Boxes Per Pallet

30.44 Pounds (13806.52 Grams) **Box Weight**

Square Yards Per Box Square Meters Per Box 5.00 **Square Yards Per Pallet** 191.36 **Square Meters Per Pallet** 159.98

Single Bulletin page 3 of 4

Accessories



301 Carpet Tiles Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres) 1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

 $680 - 760 \text{ sq.ft.} / 4 \text{ Gallons } (63 - 71 \text{ m}^2 / 15 \text{ L})$

Non-Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m^2 / 15 L)

- **☑** SDS 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Specifications 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Label 301 Pressure Sensitive Carpet Tile Adhesive



Single Bulletin page 4 of 4