Signal 1585 Engineered Hardwood • Hilltop

Benefits

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

CARB II Certified for protection from exposure to toxic air contaminants

Environmentally-Friendly Reduced eco footprint

CARB II Certified for protection from exposure to toxic air contaminants

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Performant and durable construction BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Can be sanded and refinished Adds value to your home

Resistant to normal changes in temperature - can be installed in basement

Easy and versatile Installation Coordinating moldings available

Can be installed floating, glued or nailed/stapled Compatible with embedded radiant heating Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Matte finish

Designers' Choice - This product showcase the latest trends in terms of color variations

Oil finish for the most natural look and texture Authentic handscraped and brushed finish.

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 3

Signal 1585 Engineered Hardwood • Hilltop

Product Specifications

Market Segments Builder, Pro, Residential

BrandUrbanTerraCollectionHilltopStyle NameSignalStyle Number1585

Construction Engineered Hardwood

Format Plank
Abrasion Resistance Residential Use
Species European White Oak

Grade Antique
Core Birch & Eucalyptus

 Width
 7.48" (190 mm)

 Total Thickness
 0.472" (12 mm)

 Wood Veneer Thickness
 0.0790" (2.0000 mm)

Wood Veneer Sliced

Edges 4-Sided Micro Bevel Locking System Tongue & Groove

Finish Authentically Handscraped And Wire-

Brushed

Top Surface UV-Cured Oil

Gloss Matte
Pattern Repeat n/a
Formaldehyde n/a

Installation Methods

Length Random (Variées)

Certifications FloorScore, BLC Certification,

Designers' Choice, CARB II Compliant Staple, Floating, Compatible with

embedded radiant heating, Glued, Nail

/ Staple

Engineered Hardwood

☑ Installation Guide Tongue &

Groove

Wall Installation Guide -

Hardwood



Warranties

☑ Engineered Hardwood Warranty Guide

☑ Engineered Hardwood Maintenance Guide (UV Oiled)

Residential use Finish 35 Years

Structural Integrity *Lifetime*No Questions Asked
Replacement *30 days*



Single Bulletin page 2 of 3

Signal 1585 Engineered Hardwood • Hilltop

Packaging information

Units Per Box Boxes Per Pallet

Box Weight 52.21 Pounds (23684.03 Grams)

Square Meters Per Box 2.89 **Square Meters Per Pallet** 144.40 **Square Feet Per Box** 31.09 Square Feet Per Pallet 1554.32

Moldings



Flushmount Reducer Coordinating 92" X 0.472" X 2"

(2337 mm X 12 mm X 51 mm)



Flushmount Square Nose

Coordinating 92" X 0.472" X 2.125"

(2337 mm X 12 mm X 54 mm)



Flushmount T-Molding

Coordinating 92" X 0.472" X 2"

(2337 mm X 12 mm X 51 mm)

Single Bulletin page 3 of 3