

Signal 1585

Engineered Hardwood • Hilltop

This product has been discontinued and is no longer part of our regular line.

Benefits

Safe and healthy	FloorScore® Certified for compliance with rigorous indoor air quality requirements CARB II Certified for protection from exposure to toxic air contaminants
Environmentally-Friendly	Reduced eco footprint CARB II Certified for protection from exposure to toxic air contaminants FloorScore® Certified for compliance with rigorous indoor air quality requirements
Performant and durable construction	BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards. Can be sanded and refinished Adds value to your home Resistant to normal changes in temperature - can be installed in basement
Easy and versatile Installation	Coordinating moldings available Can be installed floating, glued or nailed/stapled Compatible with embedded radiant heating Can be installed on all floor levels, even on walls
Notable look	Wide and long planks Matte finish Designers' Choice - This product showcase the latest trends in terms of color variations Oil finish for the most natural look and texture Authentic handscraped and brushed finish.
Best-in-class Warranty	30 Days No Questions Asked Replacement
Quickship	Stock product for faster delivery

Signal 1585

Engineered Hardwood • Hilltop

Product Specifications

Market Segments	Builder, Pro, Residential
Collection	Hilltop
Style Name	Signal
Style Number	1585
Construction	Engineered Hardwood
Format	Plank
Abrasion Resistance	Residential Use
Species	European White Oak
Grade	Antique
Core	Birch & Eucalyptus
Width	7.48" (190 mm)
Total Thickness	0.472" (12 mm)
Wood Veneer Thickness	0.0790" (2.0000 mm)
Wood Veneer	Sliced
Edges	4-Sided Micro Bevel
Locking System	Tongue & Groove
Finish	Authentically Handscraped And Wire-Brushed
Top Surface	UV-Cured Oil
Gloss	Matte
Pattern Repeat	n/a
Formaldehyde	n/a
Length	Random (Variées)
Certifications	FloorScore, BLC Certification, Designers' Choice, CARB II Compliant
Installation Methods	Staple, Floating, Compatible with embedded radiant heating, Glued, Nail / Staple

[Engineered Hardwood Installation Guide Tongue & Groove](#)

[Wall Installation Guide - Hardwood](#)



Warranties

- [Engineered Hardwood Warranty Guide](#)
- [Engineered Hardwood Maintenance Guide \(UV Oiled\)](#)

Residential use	Structural Integrity <i>Lifetime</i>
	No Questions Asked
	Replacement <i>30 days</i>
	Finish <i>35 Years</i>

Signal 1585

Engineered Hardwood • Hilltop

Packaging information

Units Per Box	0
Boxes Per Pallet	50
Box Weight	52.21 pounds (23684.03 grams)
Square Meters Per Box	2.89
Square Meters Per Pallet	144.40
Square Feet Per Box	31.09
Square Feet Per Pallet	1554.32

Moldings



Flushmount Reducer

Coordinating

92" X 0.472" X 2"

(2337 mm X 12 mm X 51 mm)



Flushmount Square Nose

Coordinating

92" X 0.472" X 2.125"

(2337 mm X 12 mm X 54 mm)



Flushmount T-Molding

Coordinating

92" X 0.472" X 2"

(2337 mm X 12 mm X 51 mm)