

Sarandon 1610

Engineered Hardwood • Casting

Benefits

Safe and healthy

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Environmentally-Friendly

Reduced eco footprint

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Performant and durable construction

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Protective coating for improved scratch and wear resistance

Adds value to your home

Resistant to normal changes in temperature - can be installed in basement

Easy and versatile Installation

Coordinating moldings available

Can be installed floating, glued or nailed/stapled

Compatible with embedded radiant heating

Can be installed on all floor levels, even on walls

Notable look

Wide and long planks

Matte finish

Designers' Choice - This product showcase the latest trends in terms of color variations

Best-in-class Warranty

30 Days No Questions Asked Replacement

Quickship

Stock product for faster delivery

Sarandon 1610

Engineered Hardwood • Casting

Product Specifications

| | |
|------------------------------|---|
| Market Segments | Builder, Pro, Residential |
| Brand | UrbanTerra |
| Collection | Casting |
| Style Name | Sarandon |
| Style Number | 1610 |
| Construction | Engineered Hardwood |
| Format | Plank |
| Abrasion Resistance | Residential Use |
| Species | European White Oak |
| Grade | Classic |
| Core | Eucalyptus |
| Width | 7.48" (190 mm) |
| Total Thickness | 0.472" (12 mm) |
| Wood Veneer Thickness | 0.0790" (2.0000 mm) |
| Wood Veneer | Sliced |
| Edges | 4-Sided Micro Bevel |
| Locking System | Tongue & Groove |
| Finish | Lightly Wire-Brushed |
| Top Surface | UV-Cured Urethane |
| Gloss | Matte |
| Pattern Repeat | n/a |
| Formaldehyde | TSCA Title VI |
| Length | Random (Variées) |
| Certifications | FloorScore, BLC Certification, QuickShip, TSCA Title VI Compliant |
| Installation Methods | Floating, Compatible with embedded radiant heating, Glued, Nail / Staple |

[Engineered Hardwood Installation Guide Tongue & Groove](#)

[Wall Installation Guide - Hardwood](#)



Warranties

- [Engineered Hardwood Warranty Guide](#)
- [Engineered Hardwood Maintenance Guide \(UV Cured Urethane\)](#)

Residential use

Finish *35 Years*
Structural Integrity *Lifetime*
No Questions Asked
Replacement *30 days*

Sarandon 1610

Engineered Hardwood • Casting

Packaging information


| | |
|---------------------------------|-------------------------------|
| Units Per Box | 8 |
| Boxes Per Pallet | 45 |
| Box Weight | 54.08 Pounds (24529.89 Grams) |
| Square Meters Per Box | 2.89 |
| Square Meters Per Pallet | 129.96 |
| Square Feet Per Box | 31.09 |
| Square Feet Per Pallet | 1398.87 |

Moldings



Flushmount Reducer

Coordinating
92" X 0.472" X 2"
(2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose - Round

Coordinating
92" X 0.472" X 3.110"
(2337 mm X 12 mm X 79 mm)



T-Molding

Coordinating
92" X 0.472" X 2"
(2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose - Square

Coordinating
92" X 0.472" X 3.110"
(2337 mm X 12 mm X 79 mm)