

Sarandon 1610

Engineered Hardwood • Casting

Benefits

Safe and healthy

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Environmentally-Friendly

Reduced eco footprint

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Performant and durable construction

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Protective coating for improved scratch and wear resistance

Ads value to your home

Resistant to normal changes in temperature - can be installed in basement

Easy and versatile Installation

Coordinating moldings available

Can be installed floating, glued or nailed/stapled

Compatible with embedded radiant heating

Can be installed on all floor levels, even on walls

Notable look

Wide and long planks

Matte finish

Designers' Choice - This product showcase the latest trends in terms of color variations

Best-in-class Warranty

30 Days No Questions Asked Replacement

Quickship

Stock product for faster delivery

Sarandon 1610

Engineered Hardwood • Casting

Product Specifications

Market Segments	Builder, Pro, Residential
Brand	UrbanTerra
Collection	Casting
Style Name	Sarandon
Style Number	1610
Construction	Engineered Hardwood
Format	Plank
Abrasion Resistance	Residential Use
Species	European White Oak
Grade	Classic
Core	Eucalyptus
Width	7.48" (190 mm)
Total Thickness	0.472" (12 mm)
Wood Veneer Thickness	0.0790" (2.0000 mm)
Wood Veneer	Sliced
Edges	4-Sided Micro Bevel
Locking System	Tongue & Groove
Finish	Lightly Wire-Brushed
Top Surface	UV-Cured Urethane
Gloss	Matte
Pattern Repeat	n/a
Formaldehyde	TSCA Title VI
Length	Random (Variées)
Certifications	FloorScore, BLC Certification, QuickShip, TSCA Title VI Compliant
Installation Methods	Floating, Compatible with embedded radiant heating, Glued, Nail / Staple

[Engineered Hardwood Installation Guide Tongue & Groove](#)

[Wall Installation Guide - Hardwood](#)



Warranties

- [Engineered Hardwood Warranty Guide](#)
- [Engineered Hardwood Maintenance Guide \(UV Cured Urethane\)](#)

Residential use

Finish *35 Years*
Structural Integrity *Lifetime*
No Questions Asked
Replacement *30 days*

Sarandon 1610

Engineered Hardwood • Casting

Packaging information

Units Per Box	8
Boxes Per Pallet	45
Box Weight	54.08 Pounds (24529.89 Grams)
Square Meters Per Box	2.89
Square Meters Per Pallet	129.96
Square Feet Per Box	31.09
Square Feet Per Pallet	1398.87

Moldings



Flushmount Reducer

Coordinating
92" X 0.472" X 2"
(2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose - Round

Coordinating
92" X 0.472" X 3.110"
(2337 mm X 12 mm X 79 mm)



T-Molding

Coordinating
92" X 0.472" X 2"
(2337 mm X 12 mm X 51 mm)



Flushmount Stair Nose - Square

Coordinating
92" X 0.472" X 3.110"
(2337 mm X 12 mm X 79 mm)