Francium Xtra 8032 Laminate • Atomic Xtra

Benefits

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

Budget-friendly

Water-resistant – 72-hour spill protection Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Made in Europe

Water-resistant laminate that can be installed in kitchens and half bathrooms

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains Water-resistant – 72-hour spill protection

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Wide and long planks

Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 3

Francium Xtra 8032 Laminate • Atomic Xtra

Product Specifications

Market Segments Builder, Hospitality, Pro, Property

Management, Residential, Workspace

BrandHydraPlanksSub CategoryWater-ResistantCollectionAtomic XtraStyle NameFrancium Xtra

Style Number8032ConstructionLaminateFormatPlank

Abrasion Resistance AC4 Class 32: General Commercial

Use

Species Elm

Width 7.598" (193 mm)

Total Thickness 0.315" (8 mm)

Edges 4-Sided Micro Bevel

Locking System Välinge 5G: Drop Lock

Attached Backing No Backing Thickness None

Finish Lightly Embossed - Extreme Mat

Top Surface Aluminum Oxide

Gloss Matte
Pattern Repeat 10
IIC n/a
STC n/a

Installation Methods

Formaldehyde TSCA Title VI Length 54.331" (1380 mm)

Certifications FloorScore, BLC Certification,

QuickShip, TSCA Title VI Compliant Floating, Compatible with embedded

radiant heating

Laminate Installation Guide

(Drop Lock)

Wall Installation Guide -

Laminate

Laminate Installation Video - Välinge 5G Locking System



Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use Stain Lifetime

Wear *Lifetime*No Questions Asked
Replacement *30 days*Fade *Lifetime*

NA C - D C

Manufacturing Defects

Lifetime

Commercial use Manufacturing Defects 5 Years

Wear 5 Years Stain 5 Years Fade 5 Years

Light commercial use Stain 15 Years

Fade 15 Years

Manufacturing Defects 15

Years

Wear 15 Years



Single Bulletin page 2 of 3

Francium Xtra 8032 Laminate • Atomic Xtra

Packaging information

Units Per Box 9
Boxes Per Pallet 5

Box Weight 36.88 pounds (16728.34 grams)

Square Meters Per Box2.40Square Meters Per Pallet134.19Square Feet Per Box25.79Square Feet Per Pallet1444.42

Moldings



ReducerCoordinating
94" X 0.500" X 1.625"
(2350 mm X 12.7 mm X 41.275

mm)



Stair Nose MdfCoordinating
94" X 0.750" X 2.1"
(2350 mm X 19 mm X 53.34 mm)



T-MoldingCoordinating
94" X 0.315" X 1.593"
(2350 mm X 8 mm X 40.481 mm)

Single Bulletin page 3 of 3