Benefits

Family friendly (including pet) 100% Waterproof

Easy to clean

Stain resistant, including pet stains

Budget-friendly

Safe and healthy Antimicrobial protective treatment to inhibit the growth of mold and mildew.

Phthalates Free products meaning that they will not affect your quality of life FloorScore® Certified for compliance with rigorous indoor air quality requirements

E1 Certified meaning that the product meets the European standard for indoor air quality

Slip resistant

Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful

substances.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Made in Europe

Protective polyurethane lacquer for superior resistance to wear and scratches

Easy maintenance 100% Waterproof

Antimicrobial, anti-mold and anti-fungal

Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Compatible with embedded radiant heating

Can be installed on all floor levels

Glued installation for a permanent and sturdy setup Loose lay installation possible up to 432 sq.ft (40 sq.m)

Quiet and comfortable Cushioned for comfort and warmth underfoot

Reduces noise

Notable look Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement



Single Bulletin page 1 of 4

Product Specifications

Market SegmentsResidentialBrandTexCollectionTex Pro

Style Name Monolith Dark Grey

Style Number B0110
Construction Sheet Vinyl
Format Sheet

Standard Length

Abrasion Resistance Heavy Residential & General

Commercial Use 98.40 Ft (30.00 M) Virgin PVC

 Material
 Virgin PVC

 Width
 13' 1" (4 M)

 Total Thickness
 0.118" (3 mm)

 Wear Layer Thickness
 0.0220" (0.5500 mm)

InterlayerFiberglassBackingTex BacFinishSoftwoodTop SurfacePolyurethanePattern Repeatn/a

Installation Pattern Repeat ± 78.74" W x 59.06" L (± 200.00 cm W

x 150.00 cm L)

Pattern Repeat Position n/a

Incomplete design left0.00 in (0.00 cm)Incomplete design right0.00 in (0.00 cm)Incomplete design total0.00 in (0.00 cm)DesignConcreteDesign Size (W x L)n/aReverse SeamNo

Certifications Virgin PVC, FloorScore, Phthalates

Free, BLC Certification

Installation Methods Loose lay up to 432 sq. ft. (40 sq. m.),

Compatible with embedded radiant

heating, Glued

☑ Sheet Vinyl Installation Guide



Warranties

☑ Sheet Vinyl Warranty Guide

☑ Sheet Vinyl Care & Maintenance Guide

Residential use Stain Lifetime

Wear Lifetime
Tear Lifetime
Waterproof Lifetime
Scuffing Lifetime
No Questions Asked
Replacement 30 days
Petproof Lifetime
Fade Lifetime
Indent Lifetime

Manufacturing Defects

Lifetime

Commercial use Tear 7 Years

Fade 7 Years Stain 7 Years

Manufacturing Defects 7 Years

Indent 7 Years
Waterproof Lifetime
Scuffing 7 Years
Petproof Lifetime
Wear 7 Years



Single Bulletin page 2 of 4

Packaging information

Weight

59.00 oz./y² (2000.0 g/m²)



Single Bulletin page 3 of 4

Accessories



Beauflor Adhesive - 4 Gallons

4 Gallons (15.14 Litres) 1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

220 to 260 sq. ft. / gal (20 to 24 m² / gal)

Non-Porous Coverage

220 to 260 sq.ft. / gal (20 à 24 m² / gal)

☑ Specifications - Beauflor 4N1 Adhesive

SDS - Beauflor 4N1 Adhesive



Beauflor Adhesive - 1 Gallon

1 Gallon (3.78 Litres) 1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

220 to 260 sq. ft. / gal (20 to 24 m 2 / gal)

Non-Porous Coverage

220 to 260 sq.ft. / gal (20 à 24 m 2 / gal)

☑ Specifications - Beauflor 4N1 Adhesive

SDS - Beauflor 4N1 Adhesive



Beauflor Seam Sealer - 8 oz Bottle

Adhesive — 8 Ounces (227 Grams)

Non-Porous Coverage

100 ft. / 8 oz (31 m / 237 ml)

SDS - Beauflor Seam Sealer



Single Bulletin page 4 of 4