## Hendrix 1863 Engineered Hardwood • Maestro

### **Benefits**

Safe and healthy	FloorScore® Certified for compliance with rigorous indoor air quality requirements
Environmentally-Friendly	Reduced eco footprint FloorScore® Certified for compliance with rigorous indoor air quality requirements
Performant and durable construction	BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards. Protective coating for improved scratch and wear resistance Can be sanded and refinished Ads value to your home Resistant to normal changes in temperature - can be installed in basement
Easy and versatile Installation	Coordinating moldings available Can be installed floating, glued or nailed/stapled Compatible with embedded radiant heating Can be installed on all floor levels, even on walls
Notable look	Wide and long planks Matte finish
Best-in-class Warranty	30 Days No Questions Asked Replacement

Stock product for faster delivery

Quickship



### Hendrix 1863 Engineered Hardwood • Maestro

### **Product Specifications**

Market Segments Brand Collection Style Name Style Number Construction Format Abrasion Resistance Species Grade Core Width **Total Thickness** Wood Veneer Thickness Wood Veneer Edges Locking System Finish **Top Surface** Gloss Pattern Repeat Formaldehyde Length Certifications

Installation Methods

Builder, Pro, Residential UrbanTerra Maestro Hendrix 1863 Engineered Hardwood Plank **Residential Use** European White Oak Classic Eucalyptus 7.48" (190 mm) 0.709" (18 mm) 0.1180" (3.0000 mm) Dry Solid Sawn 4-Sided Micro Bevel Tongue & Groove Lightly Wire-Brushed **UV-Cured Urethane** Matte n/a **TSCA Title VI** 74.803" (1900 mm) FloorScore, BLC Certification, QuickShip, TSCA Title VI Compliant Floating, Compatible with embedded radiant heating, Glued, Nail / Staple **Engineered Hardwood** 

- Installation Guide Tongue & Groove
- ☑ Wall Installation Guide -Hardwood



#### Warranties

- C Engineered Hardwood Warranty Guide
- Engineered Hardwood Maintenance Guide (UV Cured Urethane)

**Residential use** 

Finish *35 Years* No Questions Asked Replacement *30 days* Structural Integrity *Lifetime* 



### Hendrix 1863 Engineered Hardwood • Maestro

# Packaging information

Units Per Box	5
Boxes Per Pallet	50
Box Weight	49.52 Pounds (22462.33 Grams)
Square Meters Per Box	1.80
Square Meters Per Pallet	90.25
Square Feet Per Box	19.43
Square Feet Per Pallet	971.45

# Moldings



Flushmount Reducer Coordinating 92" X 0.709" X 2.244" (2337 mm X 18 mm X 57 mm) 
 Flushmount Stair Nose - Round
 T-Molding

 Coordinating
 Coordinating

 92" X 0.709" X 3.110"
 92" X 0.709

 (2337 mm X 18 mm X 79 mm)
 (2337 mm X)

**T-Molding** Coordinating 92" X 0.709" X 2" (2337 mm X 18 mm X 51 mm)



Flushmount Stair Nose -Square Coordinating 92" X 0.709" X 3.110" (2337 mm X 18 mm X 79 mm)

