Benefits

Family friendly (including pet) 100% Waterproof

Safe and healthy

Antimicrobial protective treatment to inhibit the growth of mold and mildew.

Phthalates Free products meaning that they will not affect your quality of life FloorScore® Certified for compliance with rigorous indoor air quality requirements

E1 Certified meaning that the product meets the European standard for indoor air quality

Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful

substances.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Easy maintenance Antimicrobial, anti-mold and anti-fungal

Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Compatible with embedded radiant heating

Glued installation for a permanent and sturdy setup

Loose lay the planks for a fast installation and an easy repair

Herringbone installation possible

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Matte finish

Wide planks

Mix and match colors for a bold look

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 4

Product Specifications

Market Segments Builder, Hospitality, Pro, Residential,

Senior Living, Workspace

BrandOne2FloorSub CategoryLVPCollectionTurboStyle NameAdelaideStyle Number2336ConstructionLuxury VinylFormatPlank

Abrasion Resistance General Commercial Use

 Material
 Virgin PVC

 Width
 7.25" (184.15 mm)

 Total Thickness
 0.197" (5 mm)

 Wear Layer Thickness
 0.0220" (0.5500 mm)

InterlayerFiberglassBackingLoose Lay

Edges 4-Sided Micro Bevel

Locking System None

Finish Medium Embossed

Top Surface UV-Cured Polyurethane

Gloss Matt
Pattern Repeat 5
IIC 66
STC 67
Design Oak
Formaldehyde E1

Length 48" (1219.2 mm)

Certifications Virgin PVC, FloorScore, E1 Certified,

Phthalates Free, BLC Certification,

QuickShip

Installation Methods Loose Lay, Compatible with embedded

radiant heating, Glued

Luxury Vinyl Installation Guide

(Loose Lay)

Wall Installation Guide - Luxury

Vinyl



Warranties

☑ Luxury Vinyl Warranty Guide

Luxury Vinyl Care & Maintenance Guide

Residential use Stain Lifetime

Manufacturing Defects

Lifetime

Fade Lifetime

Fade Lifetime
Waterproof Lifetime
Petproof Lifetime
No Questions Asked
Replacement 30 days

Wear Lifetime

Commercial use Manufacturing Defects 15

Years

Fade 15 Years Waterproof Lifetime Petproof Lifetime Wear 15 Years Stain 15 Years



Single Bulletin page 2 of 4

Packaging information

Units Per Box 8
Boxes Per Pallet 7

Box Weight 35.76 Pounds (16220.68 Grams)

Square Meters Per Box1.80Square Meters Per Pallet125.71Square Feet Per Box19.33Square Feet Per Pallet1353.1

Moldings



MultitrimStair NoseCoordinatingCoordinating94" X 0.23" X 1.593"94" X 1.16" X 2"

(2350 mm X 5.842 mm X 40.481 (2350 mm X 25.4 mm X 50.80 mm)

mm)

Single Bulletin page 3 of 4

Accessories



701 Luxury Vinyl Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Non-Porous: 1/16" x 1/32" x 1/32" V-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m^2 / 15 L)

Non-Porous Coverage

1,000 to 1,200 sq.ft. / 4 U.S. Gallons (93 to 112 m 2 / 15 L)

- ☑ Label 701 Vinyl Flooring Adhesive
- SDS 701 Vinyl Flooring Adhesive
- ☑ Specifications 701 Vinyl Flooring Adhesive



Single Bulletin page 4 of 4