

Cormorant 1447

Laminate • Littora

Benefits

Safe and healthy

FloorScore® Certified for compliance with rigorous indoor air quality requirements
TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.
Heavy commercial abrasion resistance
Water-resistant laminate that can be installed in kitchens and half bathrooms
Ultra-durable and scratch-resistant surface

Easy maintenance

Easy to clean
Stain resistant, including pet stains
Water-resistant - 72-hour spill protection

Easy and versatile Installation

Floating installation
2 in 1 - comes with an attached underlayment
Compatible with embedded radiant heating
No telegraphing, even when installed over hard surface flooring
Matching moldings available
Can be installed on all floor levels, even on walls

Quiet and comfortable

Foam backing for greater temperature and sound insulation

Notable look

Wide and long planks
Matte finish

Best-in-class Warranty

30 Days No Questions Asked Replacement

Quickship

Stock product for faster delivery

Cormorant 1447

Laminate • Littora

Product Specifications

Market Segments	Hospitality, Pro, Residential, Workspace
Brand	HydraPlanks
Sub Category	Water-Resistant
Collection	Littora
Style Name	Cormorant
Style Number	1447
Construction	Laminate
Format	Plank
Abrasion Resistance	AC5 Class 33: Heavy Commercial Use
Species	Oak
Width	7.68" (195 mm)
Total Thickness	0.563" (14.3 mm)
Edges	4-Sided Micro Bevel & Wax
Locking System	Välinge 5G: Drop Lock
Attached Backing	Yes
Backing Thickness	0.079" (2 mm)
Finish	Registered Embossed
Top Surface	Aluminum Oxide
Gloss	Matte
Pattern Repeat	6
IIC	63
STC	62
Formaldehyde	TSCA Title VI
Length	47.835" (1215 mm)
Certifications	FloorScore, BLC Certification, QuickShip, TSCA Title VI Compliant
Installation Methods	Floating, Compatible with embedded radiant heating

[Laminate Installation Guide \(Drop Lock\)](#)
[Laminate Installation Video - Välinge 5G Locking System](#)



Warranties

- [Laminate Warranty Guide](#)
- [Laminate Maintenance Guide](#)

Residential use	Wear <i>Lifetime</i> Fade <i>Lifetime</i> Stain <i>Lifetime</i> No Questions Asked Replacement <i>30 days</i> Manufacturing Defects <i>Lifetime</i>
Commercial use	Fade <i>15 Years</i> Wear <i>15 Years</i> Manufacturing Defects <i>15 Years</i> Stain <i>15 Years</i>


Cormorant 1447

Laminate • Littora


Packaging information

Units Per Box	6
Boxes Per Pallet	55
Box Weight	40.54 Pounds (18390.89 Grams)
Square Meters Per Box	1.42
Square Meters Per Pallet	78.18
Square Feet Per Box	15.3
Square Feet Per Pallet	841.5


Moldings



Flushmount Stair Nose - Round
Matching
94.488" X 0.945" X 2.834"
(2400 mm X 24 mm X 72 mm)



Reducer
Matching
94.488" X 0.671" X 1.771"
(2400 mm X 17 mm X 45 mm)



T-Molding
Matching
94.488" X 0.551" X 1.771"
(2400 mm X 14 mm X 45 mm)