Benefits

Safe and healthy Antimicrobial protective treatment to inhibit the growth of mold and mildew.

Phthalates-Free products meaning that they will not affect your quality of life FloorScore® Certified for compliance with rigorous indoor air quality requirements E1 Certified meaning that the product meets the European standard for indoor air quality

Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful

substances.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Easy maintenance 100% Waterproof

Antimicrobial, anti-mold and anti-fungal

Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Compatible with embedded radiant heating

Glued installation for a permanent and sturdy setup

Herringbone installation possible

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Matte finish

Designers' Choice - This product showcase the latest trends in terms of color variations

Mix and match colors for a bold look

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 4

Product Specifications

Market Segments Builder, Hospitality, Pro, Residential,

Senior Living, Workspace

BrandPermaLuxeSub CategoryLVPCollectionVariaStyle NameContrastStyle Number2118ConstructionLuxury VinylFormatPlank

Abrasion Resistance General Commercial Use

 Material
 Virgin PVC

 Width
 7.362" (187 mm)

 Total Thickness
 0.118" (3 mm)

 Wear Layer Thickness
 0.0220" (0.5500 mm)

InterlayerNoneBackingDry Back

Edges 4-Sided Micro Bevel

Locking System None

Finish Lightly Embossed

Top Surface UV-Cured Polyurethane & Ceramic

Bead Technology

Gloss Matte
Pattern Repeat 5
IIC 62
STC 68

STC 68

Design Wood

Formaldehyde E1

Installation Methods

Length 48.307" (1227 mm)

Certifications Virgin PVC, FloorScore, E1 Certified,

BLC Certification, QuickShip, Phthalates-Free, Designers' Choice Herringbone, Compatible with

embedded radiant heating, Glued

Luxury Vinyl Installation Guide

(DryBack)

Wall Installation Guide - Luxury

Vinyl



Warranties

☑ Luxury Vinyl Warranty Guide

Luxury Vinyl Care & Maintenance Guide

Residential use Wear Lifetime

Stain *Lifetime*

Manufacturing Defects

Lifetime
Fade Lifetime
Waterproof Lifetime
Petproof Lifetime
No Questions Asked
Replacement 30 days

Commercial use Stain 15 Years

Manufacturing Defects 15

Years

Fade 15 Years Waterproof Lifetime Petproof Lifetime Wear 15 Years



Single Bulletin page 2 of 4

Packaging information

Units Per Box 14 Boxes Per Pallet 55

Box Weight 41.84 Pounds (18979.11 Grams)

Square Meters Per Box3.21Square Meters Per Pallet176.69Square Feet Per Box34.58Square Feet Per Pallet1901.9

Moldings

Slimtrim



Versaedge Stair Nose

Coordinating Coordinating 94" X 0.250" X 2" 94" X 1" X 2"

(2350 mm X 6.35 mm X 51 mm) (2350 mm X 25 mm X 51 mm)

Single Bulletin page 3 of 4

Accessories



701 Luxury Vinyl Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Non-Porous: 1/16" x 1/32" x 1/32" V-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m^2 / 15 L)

Non-Porous Coverage

1,000 to 1,200 sq.ft. / 4 U.S. Gallons (93 to 112 m 2 / 15 L)

- **☑** Label 701 Vinyl Flooring Adhesive
- SDS 701 Vinyl Flooring Adhesive
- ☑ Specifications 701 Vinyl Flooring Adhesive



Single Bulletin page 4 of 4