

Opposite T39

Carpet Tiles • Modulyss

Benefits

Safe and healthy

Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market

Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation

Slip Resistant

Cushion falls and reduces the risk of injury

Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations

Certified A+ - French regulation on VOCs (Volatile Organic Compounds) and on the obligatory labelling of building products, floor and wall covering products, and paints and varnishes used inside buildings

Environmentally-Friendly

GUT-NR certified - Strict standards, incentives to adopt eco-friendly solutions and objective information on all aspects of carpet to benefit the environment and consumers.

Made with back2back backing which contains a minimum of 70% post industrial recycled content

Made with solution-dyed fibers a process that reduces significantly water consumption

Limitless designabilities

One of the most versatile floor coverings because you get to choose from a wide range of colors and textures

Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable

Without a doubt, the most comfortable flooring

Greatest soundproofing and insulating properties

Reduces heat loss

Soft and warm to the touch

High performance

High-performing product made to withstand heavy traffic

Part of our Modulyss product offering, ideal for general commercial applications

Easy to install and repair

Easy installation with our 301 Carpet Tiles Adhesive

Modular floor covering for fast and easy repair when needed

Opposite T39

Carpet Tiles • Modulyss

Product Specifications

Market Segments	Hospitality, Pro, Workspace
Brand	Modulyss
Collection	Modulyss
Style Name	Opposite
Style Number	T39
Colors	11
Construction	Minituft Loop
Format	Tile
Fiber Type	100% BCF Nylon
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	14.75 oz./y ² (500.0 g/m ²)
Pile Height	3/64 in (1.1 mm)
Total Height	15/64 in (5.9 mm)
Backing	Back2Back Modified Bitumen
Stitch Count	0/in (0/10 cm)
Gauge	5/64 in (1.98 mm)
Density Factor	12259
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70 & C.G.S.B. 4-GP-129
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	n/a
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, Certified A+, GUT-NR
Installation Methods	Quarter Turn
	Modulyss Carpet Tiles Installation Guide



Color Names & Numbers

#0535	O535	#0553	O553
#0579	O579	#0817	O817
#0847	O847	#0907	O907
#0915	O915	#0942	O942
#0983	O983	#0989	O989
#0991	O991		

Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Dimensional Stability <i>15 Years</i>
	Colorfastness <i>15 Years</i>
	Manufacturing Defects <i>15 Years</i>
	Stain Resistance <i>15 Years</i>
	Static Control <i>15 Years</i>
	Wear Resistance <i>15 Years</i>
	Edge Ravelling <i>15 Years</i>
	Delamination Resistance <i>15 Years</i>
	Anti-Zippering <i>15 Years</i>


Opposite T39

Carpet Tiles • Modulyss


Colors




#O535
O535
Dropped Product




#O553
O553
Dropped Product




#O579
O579
Dropped Product




#O817
O817
Dropped Product




#O847
O847
Dropped Product




#O907
O907
Dropped Product




#O915
O915
Dropped Product




#O942
O942
Dropped Product



#O983
O983
Dropped Product



#O989
O989
Dropped Product



#O991
O991
Dropped Product

Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	50.71 pounds (23001.83 grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99