Fluorine 8013 Laminate • Atomic

Benefits

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

Budget-friendly

Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and that are compliant to the new standards of the EPA.

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Made in Europe

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Wide and long planks

Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 3

Fluorine 8013 Laminate • Atomic

Product Specifications

Market Segments Builder, Pro, Property Management,

Residential **Sub Category** Regular Collection Atomic Style Name Fluorine Style Number 8013 Construction Laminate Format Plank

Abrasion Resistance AC4 Class 32: General Commercial

Species Oak

Width 7.598" (193 mm) **Total Thickness** 0.315" (8 mm)

Core Thickness Backing n/a

Edges 4-Sided Micro Bevel **Locking System** Välinge 5G: Drop Lock

Attached Backing Backing Thickness None

Finish Lightly Embossed - Extreme Mat

Top Surface Aluminum Oxide

Gloss Matte Pattern Repeat 10 IIC n/a STC

Formaldehyde TSCA Title VI 54.331" (1380 mm) Length

Certifications FloorScore, BLC Certification,

QuickShip, TSCA Title VI Compliant

Installation Methods Floating, Compatible with embedded

radiant heating

Laminate Installation Guide (Drop Lock)

Wall Installation Guide -

Laminate

Laminate Installation Video -Välinge 5G Locking System



Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use Manufacturing Defects

> Lifetime Wear Lifetime Stain Lifetime No Questions Asked Replacement 30 days Fade Lifetime

Commercial use Stain 5 Years

Wear 5 Years

Manufacturing Defects 5 Years

Fade 5 Years

Light commercial use Stain 15 Years

Wear 15 Years Fade 15 Years

Manufacturing Defects 15

Years



Single Bulletin page 2 of 3

Fluorine 8013 Laminate • Atomic

Packaging information

Units Per Box 9
Boxes Per Pallet 5

Box Weight 36.88 pounds (16728.34 grams)

Square Meters Per Box2.40Square Meters Per Pallet134.19Square Feet Per Box25.79Square Feet Per Pallet1444.42

Moldings



Stair Nose MdfCoordinating
94" X 0.750" X 2.1"
(2388 mm X 19 mm X 53.34 mm)

T-MoldingCoordinating
94" X 0.315" X 1.750"
(2388 mm X 8 mm X 44.45)



Single Bulletin page 3 of 3