

Dynamo TDYN

Carpet Tiles • Mainstreet Tiles - Nyluxe

Benefits

Safe and healthy

Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market
Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation
Slip Resistant
Cushion falls and reduces the risk of injury
Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations

Environmentally-Friendly

Made with solution-dyed fibers a process that reduces significantly water consumption

Best-in-class Warranty

30 Days No Questions Asked Replacement

Limitless designabilities

One of the most versatile floor coverings because you get to choose from a wide range of colors and textures
Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable

Without a doubt, the most comfortable flooring
Greatest soundproofing and insulating properties
Reduces heat loss
Soft and warm to the touch

Quickship

Stock product for faster delivery

Stain resistant & easy to clean

Protected with Stain Control for resistance to the most stubborn stains
Treated with SoilScreen to keep soil on the surface making your carpet easier to clean

High performance

Made with our Nyluxe solution-dyed nylon fiber for outstanding wear resistance
Part of our Mainstreet Nyluxe product offering, ideal for general commercial applications
Made with EnduroBac backing which provides strong and non-fraying edge and offers durability and exceptional dimensional stability

Easy to install and repair

Easy installation with our 301 Carpet Tiles Adhesive
Modular floor covering for fast and easy repair when needed

Dynamo TDYN

Carpet Tiles • Mainstreet Tiles - Nyluxe

Product Specifications

Market Segments	Builder, Hospitality, Pro, Property Management, Residential, Senior Living, Workspace
Brand	Nyluxe Tiles
Collection	Mainstreet Tiles - Nyluxe
Style Name	Dynamo
Style Number	TDYN
Colors	6
Construction	Multi-Level Loop
Format	Tile
Fiber Type	100% Solution Dyed Nylon 6
Abrasion Resistance	General Commercial Use
Dye Method	Solution Dyed
Pile Weight	15.31 oz./y ² (519.0 g/m ²)
Pile Height	11/64 in (4.0 mm)
Total Height	9/32 in (7.0 mm)
Backing	Endurobac
Stitch Count	13 /in (52 /10 cm)
Gauge	1/10 in (2.54 mm)
Density Factor	3498
Static Control	Less Than 3.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	GLP 3325
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, QuickShip, SoilScreen, Stain Control
Installation Methods	Quarter Turn

[🔗 Carpet Tiles Installation Guide](#)



Color Names & Numbers

#T546	Straw Basket	#T547	Mysterious Taupe
#T556	Deep Space	#T573	Mixed Metal
#T575	Gloomy Night	#T578	Black Spider

Warranties

[🔗 Carpet Tiles Warranty Guide](#)

[🔗 Carpet Tiles Care & Maintenance Guide](#)

Residential use	No Questions Asked Replacement <i>30 days</i> Stain Resistance <i>Lifetime</i> Static Control <i>Lifetime</i> Wear Resistance <i>Lifetime</i> Edge Ravelling <i>Lifetime</i> Anti-Zippering <i>Lifetime</i> Dimensional Stability <i>Lifetime</i> Delamination Resistance <i>Lifetime</i>
Commercial use	Static Control <i>15 Years</i> Delamination Resistance <i>15 Years</i> Dimensional Stability <i>15 Years</i> Anti-Zippering <i>15 Years</i> Wear Resistance <i>15 Years</i> Edge Ravelling <i>15 Years</i> Stain Resistance <i>15 Years</i>


Dynamo TDYN

Carpet Tiles • Mainstreet Tiles - Nyluxe

Colors




#T546
Straw Basket



#T547
Mysterious Taupe



#T556
Deep Space



#T573
Mixed Metal



#T575
Gloomy Night



#T578
Black Spider

Packaging information

Units Per Box	20
Boxes Per Pallet	28
Box Weight	51.55 Pounds (23381.58 Grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	167.44
Square Meters Per Pallet	139.98

Dynamo TDYN

Carpet Tiles • Mainstreet Tiles - Nyluxe

Accessories



301 Carpet Tiles Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

Non-Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

- [SDS - 301 Pressure Sensitive Carpet Tile Adhesive](#)
- [Specifications - 301 Pressure Sensitive Carpet Tile Adhesive](#)
- [Label - 301 Pressure Sensitive Carpet Tile Adhesive](#)