

Sandford 6018

Engineered Luxury Vinyl • Adventure

Benefits

Safe and healthy

Antimicrobial protective treatment to inhibit the growth of mold and mildew.
Phthalates-Free products meaning that they will not affect your quality of life
FloorScore® Certified for compliance with rigorous indoor air quality requirements
E1 Certified meaning that the product meets the European standard for indoor air quality
Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful substances.

Performant and durable construction

Commercial abrasion resistance
BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.
Innovative construction for a long-lasting and great-looking floorcovering (WPC)

Easy maintenance

100% Waterproof
Antimicrobial, anti-mold and anti-fungal
Easy to clean
Stain resistant, including pet stains

Easy and versatile Installation

Floating installation
2 in 1 - comes with an attached underlayment
Compatible with embedded radiant heating
Can be installed on all floor levels
No telegraphing, even when installed over hard surface flooring
Minimal floor preparation
Matching moldings available

Quiet and comfortable

Cork backing for greater temperature and sound insulation
High soundproofing ratings (IIC/STC)

Notable look

Matte finish

Best-in-class Warranty

30 Days No Questions Asked Replacement

Quickship

Stock product for faster delivery

Sandford 6018

Engineered Luxury Vinyl • Adventure

Product Specifications

Market Segments	Pro, Property Management, Residential
Brand	HydraLuxe
Sub Category	WPC
Collection	Adventure
Style Name	Sandford
Style Number	6018
Construction	Engineered Luxury Vinyl
Format	Plank
Abrasion Resistance	General Commercial Use
Material	Virgin PVC
Core Material	70% Virgin PVC / 30% Calcium Carbonate
Width	7.087" (180 mm)
Total Thickness	0.307" (7.8 mm)
Wear Layer Thickness	0.0220" (0.5500 mm)
Core Thickness	0.1770" (4.5000 mm)
Backing	Cork
Edges	4-Sided Micro Bevel
Locking System	Välinge 2G: Angle-to-Angle
Backing Thickness	0.0590" (1.5000 mm)
Finish	Registered Embossed
Top Surface	UV-Cured Acrylic
Gloss	Matte
Pattern Repeat	5
IIC	72
STC	69
Design	Oak
Formaldehyde	E1
Vinyl Thickness	0.0710" (1.8000 mm)
Length	48.031" (1220 mm)
Certifications	Virgin PVC, FloorScore, E1 Certified, Phthalates-Free, BLC Certification, QuickShip
Installation Methods	Floating, Compatible with embedded radiant heating

[Engineered Luxury Vinyl Installation Guide \(Angle to Angle\)](#)

[Engineered Luxury Vinyl Installation Video - Välinge 2G angle-to-angle Locking System](#)



Warranties

- [Engineered Luxury Vinyl Warranty Guide](#)
- [Engineered Luxury Vinyl Maintenance Guide](#)

Residential use	Petproof <i>Lifetime</i> No Questions Asked Replacement <i>30 days</i> Waterproof <i>Lifetime</i> Fade <i>Lifetime</i> Stain Resistance <i>Lifetime</i> Manufacturing Defects <i>Lifetime</i> Wear <i>Lifetime</i>
Commercial use	Stain Resistance <i>15 Years</i> Fade <i>15 Years</i> Wear <i>15 Years</i> Manufacturing Defects <i>15 Years</i> Waterproof <i>Lifetime</i> Petproof <i>Lifetime</i>

Sandford 6018

Engineered Luxury Vinyl • Adventure

Packaging information

Units Per Box	8
Boxes Per Pallet	65
Box Weight	30.63 Pounds (13895.43 Grams)
Square Meters Per Box	1.76
Square Meters Per Pallet	114.19
Square Feet Per Box	18.91
Square Feet Per Pallet	1229.15

Moldings



Reducer
Matching
94.488" X 0.413" X 1.771"
(2400 mm X 10.5 mm X 45 mm)



T-Molding
Matching
94.488" X 0.413" X 1.771"
(2400 mm X 10.5 mm X 45 mm)



Flushmount Stair Nose - Round
Matching
94.488" X .984" X 4.330"
(2400 mm X 25 mm X 110 mm)



Flushmount Stair Nose - Square
Matching
94.488" X 1.299" X 4.449"
(2400 mm X 33 mm X 113 mm)