Benefits

| Safe and healthy | Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market |
|---------------------------------|---|
| | Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation |
| | Slip Resistant |
| | Cushion falls and reduces the risk of injury |
| | Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations |
| | |
| Environmentally-Friendly | Made with solution-dyed fibers a process that reduces significantly water consumption |
| Best-in-class Warranty | 30 Days No Questions Asked Replacement |
| Limitless designabilities | One of the most versatile floor coverings because you get to choose from a wide range of colors and textures |
| | Easy to mix and match colors and designs for a personalized look |
| Warm, quiet and comfortable | Without a doubt, the most comfortable flooring |
| | Greatest soundproofing and insulating properties |
| | Reduces heat loss |
| | Soft and warm to the touch |
| Quickship | Stock product for faster delivery |
| Stain resistant & easy to clean | Protected with Stain Control for resistance to the most stubborn stains |
| | Treated with SoilScreen to keep soil on the surface making your carpet easier to clean |
| High performance | Made with our Nyluxe solution-dyed nylon fiber for outstanding wear resistance |
| | Part of our Mainstreet Nyluxe product offering, ideal for general commercial applications |
| | Made with EnduroBac backing which provides strong and non-fraying edge and offers durability and |
| | exceptional dimensional stability |
| Easy to install and repair | Easy installation with our 301 Carpet Tiles Adhesive |
| | Modular floor covering for fast and easy repair when needed |



Product Specifications

Market Segments

Brand Collection Style Name Style Number Colors Construction Format Fiber Type Abrasion Resistance Dye Method Pile Weight Pile Height **Total Height** Backing Stitch Count Gauge **Density Factor** Static Control Flammability

Flooring Radiant Panel Tarr Indoor Air Quality Dimension Color Fastness Certifications

Installation Methods

Builder, Hospitality, Pro, Property Management, Residential, Senior Living, Workspace Nyluxe Tiles Mainstreet Tiles - Nyluxe Fascination TFAS 5 Multi-Level Loop Plank 100% Solution Dyed Nylon General Commercial Use Solution Dyed 20.00 oz./y² (678.1 g/m²) 11/64 in (4.0 mm) 9/32 in (7.0 mm) Endurobac 11 /in (42 /10 cm) 1/12 in (2.11 mm) 7200 Less Than 2.0 kV (AATCC 134) Meets DOC FF-1-70 & C.G.S.B. 4-GP-129 Class 1 (ASTM E-648) 3 GLP 3325 19.7 x 39.4" (50 cmx100 cm) Meets 5.0 AATCC 16 Green Label Plus, QuickShip, Environmental Product Declaration (EPD), SoilScreen, Stain Control Herringbone, Ashlar, Quarter Turn

Carpet Tiles Installation Guide

(planks)



Color Names & Numbers

| #01 | Escalate | #02 | Gradient Blue |
|-----|--------------|-----|---------------|
| #03 | Inclination | #04 | Downhill |
| #05 | Leaning Grey | | |

Warranties

- ☑ Carpet Tiles Warranty Guide
- Carpet Tiles Care & Maintenance Guide

Residential use


Commercial use


Edge Ravelling *Lifetime* Delamination Resistance *Lifetime* Dimensional Stability *Lifetime* Anti-Zippering *Lifetime* No Questions Asked Replacement *30 days* Stain Resistance *Lifetime* Static Control *Lifetime* Wear Resistance *Lifetime* Delamination Resistance *15*


Years Stain Resistance 15 Years Static Control 15 Years Wear Resistance 15 Years Edge Ravelling 15 Years Dimensional Stability 15 Years Anti-Zippering 15 Years



Colors









Inclination

Downhill

Leaning Grey

Packaging information

| Units Per Box | 10 |
|--------------------------|-------------------------------|
| Boxes Per Pallet | 28 |
| Box Weight | 53.82 Pounds (24412.32 Grams) |
| Square Yards Per Box | 5.98 * |
| Square Meters Per Box | 5.00 * |
| Square Yards Per Pallet | 167.44 * |
| Square Meters Per Pallet | 139.98 * |
| | |

* The number of boxes per skid may vary between 28 boxes (167.44 SY) and 32 boxed (191.36 SY), depending on the assigned product. Exact quantity will be confirmed when the order is placed.



Accessories



301 Carpet Tiles Adhesive - 4 U.S. Gallons 4 Gallons (15.14 Litres) 1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage 680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

Non-Porous Coverage 680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

- ☑ SDS 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Specifications 301 Pressure Sensitive Carpet Tile Adhesive
- ☑ Label 301 Pressure Sensitive Carpet Tile Adhesive

