## Cohen 1861 Engineered Hardwood • Maestro

### **Benefits**

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

Environmentally-Friendly Reduced eco footprint

FloorScore® Certified for compliance with rigorous indoor air quality requirements

Performant and durable construction BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Protective coating for improved scratch and wear resistance

Can be sanded and refinished Ads value to your home

Resistant to normal changes in temperature - can be installed in basement

Easy and versatile Installation Coordinating moldings available

Can be installed floating, glued or nailed/stapled Compatible with embedded radiant heating Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Matte finish

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 3

## Cohen 1861 Engineered Hardwood • Maestro

## **Product Specifications**

Market Segments Builder, Pro, Residential

BrandUrbanTerraCollectionMaestroStyle NameCohenStyle Number1861

Construction Engineered Hardwood

Format Plank

Abrasion Resistance Residential Use
Species European White Oak

Grade Classic Core Eucalyptus Width 7.48" (190 mm) **Total Thickness** 0.709" (18 mm) **Wood Veneer Thickness** 0.1180" (3.0000 mm) Wood Veneer Dry Solid Sawn Edges 4-Sided Micro Bevel **Locking System** Tongue & Groove Finish Lightly Wire-Brushed **Top Surface UV-Cured Urethane** 

Gloss Matte
Pattern Repeat n/a

Formaldehyde TSCA Title VI Length 74.803" (1900 mm)

**Certifications** FloorScore, BLC Certification,

QuickShip, TSCA Title VI Compliant
Installation Methods Floating, Compatible with embedded
radiant heating, Glued, Nail / Staple

**Engineered Hardwood** 

☑ Installation Guide Tongue & Groove

...

Wall Installation Guide -

Hardwood



#### Warranties

☑ Engineered Hardwood Warranty Guide

Engineered Hardwood Maintenance Guide (UV Cured Urethane)

Residential use

Finish 35 Years
No Questions Asked
Replacement 30 days
Structural Integrity Lifetime



Single Bulletin page 2 of 3

### **Cohen 1861** Engineered Hardwood • Maestro

# Packaging information

**Units Per Box Boxes Per Pallet** 

**Box Weight** 49.52 Pounds (22462.33 Grams)

Square Meters Per Box 1.80 **Square Meters Per Pallet** 90.25 **Square Feet Per Box** 19.43 **Square Feet Per Pallet** 971.45

### Moldings



Flushmount Reducer

Coordinating 92" X 0.709" X 2.244"

(2337 mm X 18 mm X 57 mm)



Flushmount Stair Nose - Round T-Molding

Coordinating 92" X 0.709" X 3.110"

(2337 mm X 18 mm X 79 mm)



Coordinating 92" X 0.709" X 2"

(2337 mm X 18 mm X 51 mm)



Flushmount Stair Nose -Square

Coordinating 92" X 0.709" X 3.110" (2337 mm X 18 mm X 79 mm)



Single Bulletin page 3 of 3