

First Define T28

Carpet Tiles • Modulyss - First

Benefits

Safe and healthy

Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market
Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation
Slip Resistant
Cushion falls and reduces the risk of injury
Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations
Certified A+ - French regulation on VOCs (Volatile Organic Compounds) and on the obligatory labelling of building products, floor and wall covering products, and paints and varnishes used inside buildings

Environmentally-Friendly

GUT-NR certified - Strict standards, incentives to adopt eco-friendly solutions and objective information on all aspects of carpet to benefit the environment and consumers.
Made with back2back backing which contains a minimum of 70% post industrial recycled content
Made with solution-dyed fibers a process that reduces significantly water consumption

Limitless designabilities

One of the most versatile floor coverings because you get to choose from a wide range of colors and textures
Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable

Without a doubt, the most comfortable flooring
Greatest soundproofing and insulating properties
Reduces heat loss
Soft and warm to the touch

High performance

High-performing product made to withstand heavy traffic
Part of our Modulyss product offering, ideal for general commercial applications

Easy to install and repair

Easy installation with our 301 Carpet Tiles Adhesive
Modular floor covering for fast and easy repair when needed

First Define T28

Carpet Tiles • Modulyss - First

Product Specifications

| | |
|------------------------|--|
| Market Segments | Builder, Hospitality, Pro, Property Management, Senior Living, Workspace |
| Brand | Modulyss |
| Collection | Modulyss - First |
| Style Name | First Define |
| Style Number | T28 |
| Colors | 11 |
| Construction | Tufted Loop |
| Format | Tile |
| Fiber Type | 100% Solution Dyed Nylon |
| Abrasion Resistance | Heavy commercial Use |
| Dye Method | Solution Dyed |
| Pile Weight | 17.40 oz./y ² (590.0 g/m ²) |
| Pile Height | 7/64 in (2.7 mm) |
| Total Height | 17/64 in (6.5 mm) |
| Backing | Back2Back Modified Bitumen |
| Stitch Count | 0 /in (0 /10 cm) |
| Gauge | 1/12 in (2.11 mm) |
| Density Factor | 5487 |
| Static Control | Less Than 2.0 kV (AATCC 134) |
| Flammability | Meets DOC FF-1-70 |
| Flooring Radiant Panel | Class 1 (ASTM E-648) |
| Tarr | 0 |
| Indoor Air Quality | n/a |
| Dimension | 19.7 x 19.7" (50 X 50 cm) |
| Color Fastness | n/a |
| Certifications | Green Label Plus, Certified A+, Certified CE, GUT-NR |
| Installation Methods | Quarter Turn, Monolithic, Brick |

[!\[\]\(78c10c6c1104aea28089918a14d33a59_img.jpg\) **Modulyss Carpet Tiles Installation Guide**](#)



Color Names & Numbers

| | | | |
|-------|------|-------|------|
| #D061 | D061 | #D140 | D140 |
| #D210 | D210 | #D322 | D322 |
| #D329 | D329 | #D573 | D573 |
| #D625 | D625 | #D914 | D914 |
| #D957 | D957 | #D965 | D965 |
| #D995 | D995 | | |

Warranties

- [!\[\]\(c6a8736a601a632e2c96605cf66055ed_img.jpg\) **Modulyss Carpet Tiles Warranty Guide**](#)
- [!\[\]\(64ef2b19d70b31fbbfce0e0e2aa3d7b4_img.jpg\) **Modulyss Carpet Tiles Maintenance Guide**](#)

| | |
|----------------|----------------------------------|
| Commercial use | Dimensional Stability 15 Years |
| | Colorfastness 15 Years |
| | Manufacturing Defects 15 Years |
| | Stain Resistance 15 Years |
| | Static Control 15 Years |
| | Wear Resistance 15 Years |
| | Edge Ravelling 15 Years |
| | Delamination Resistance 15 Years |
| | Anti-Zippering 15 Years |

First Define T28

Carpet Tiles • Modulyss - First


Colors



#D061
D061




#D140
D140



#D210
D210



#D322
D322



#D329
D329




#D573
D573



#D625
D625




#D914
D914



#D957
D957



#D965
D965



#D995
D995

Packaging information

| | |
|--------------------------|-------------------------------|
| Units Per Box | 20 |
| Boxes Per Pallet | 20 |
| Box Weight | 49.57 Pounds (22486.46 Grams) |
| Square Yards Per Box | 5.98 |
| Square Meters Per Box | 5.00 |
| Square Yards Per Pallet | 119.6 |
| Square Meters Per Pallet | 99.99 |