Benefits

Safe and healthy Antimicrobial protective treatment to inhibit the growth of mold and mildew.

Phthalates-Free products meaning that they will not affect your quality of life FloorScore® Certified for compliance with rigorous indoor air quality requirements

E1 Certified meaning that the product meets the European standard for indoor air quality

Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful

substances.

Performant and durable construction Light commercial abrasion resistance

BLC Certified $\ensuremath{\mathfrak{B}}$ - Ensures that the floor covering you're buying surpasses industry quality standards.

Easy maintenance 100% Waterproof

Antimicrobial, anti-mold and anti-fungal

Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Compatible with embedded radiant heating

Glued installation for a permanent and sturdy setup

Herringbone installation possible

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Matte finish

Mix and match colors for a bold look

Best-in-class Warranty 30 Days No Questions Asked Replacement

Quickship Stock product for faster delivery

Single Bulletin page 1 of 4

Product Specifications

Market Segments Pro, Property Management,

Residential, Senior Living

BrandPermaLuxeSub CategoryLVPCollectionAerialStyle NameSanta AnaStyle Number2382ConstructionLuxury VinylFormatPlank

Abrasion Resistance Heavy Residential & Light Commercial

Use

 Material
 Virgin PVC

 Width
 6" (152.4 mm)

 Total Thickness
 0.079" (2 mm)

 Wear Layer Thickness
 0.0120" (0.3000 mm)

InterlayerNoneBackingDry Back

Edges 4-Sided Micro Bevel

Locking System None

Finish Medium Embossed
Top Surface UV-Cured Polyurethane

Gloss Matte
Pattern Repeat 6
IIC n/a
STC n/a
Design Oak
Formaldehyde E1

Length 48" (1219.2 mm)

Certifications Virgin PVC, FloorScore, E1 Certified,

Phthalates-Free, BLC Certification,

QuickShip

Installation Methods Herringbone, Compatible with

embedded radiant heating, Glued

Luxury Vinyl Installation Guide (DryBack)

Wall Installation Guide - Luxury

Vinyl



Warranties

☑ Luxury Vinyl Warranty Guide

Luxury Vinyl Care & Maintenance Guide

Residential use Waterproof Lifetime

Manufacturing Defects 25

Years

Fade 25 Years Wear 25 Years Stain 25 Years Petproof Lifetime No Questions Asked Replacement 30 days

Light commercial use Stain 7 Years

Petproof *Lifetime*Waterproof *Lifetime*Wear *7 Years*Fade *7 Years*

Manufacturing Defects 7 Years

Single Bulletin page 2 of 4

Packaging information

Units Per Box 18 Boxes Per Pallet 70

Box Weight 28.08 Pounds (12736.86 Grams)

Square Meters Per Box3.34Square Meters Per Pallet234.11Square Feet Per Box36Square Feet Per Pallet2520

Moldings



MultitrimStair NoseCoordinatingCoordinating94" X 0.23" X 1.593"94" X 1.16" X 2"

 $(2350 \; mm \; X \; 5.842 \; mm \; X \; 40.481 \qquad (2350 \; mm \; X \; 25.4 \; mm \; X \; 51 \; mm)$

mm)



Single Bulletin page 3 of 4

Accessories



701 Luxury Vinyl Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Non-Porous: 1/16" x 1/32" x 1/32" V-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m^2 / 15 L)

Non-Porous Coverage

1,000 to 1,200 sq.ft. / 4 U.S. Gallons (93 to 112 m^2 / 15 L)

- **☑** Label 701 Vinyl Flooring Adhesive
- SDS 701 Vinyl Flooring Adhesive
- ☑ Specifications 701 Vinyl Flooring Adhesive



Single Bulletin page 4 of 4