

# Frame TQS2

## Carpet Tiles • Modulyss

### Benefits

#### Safe and healthy

Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market  
Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation  
Slip Resistant  
Cushion falls and reduces the risk of injury  
Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations  
Certified A+ - French regulation on VOCs (Volatile Organic Compounds) and on the obligatory labelling of building products, floor and wall covering products, and paints and varnishes used inside buildings

#### Environmentally-Friendly

GUT-NR certified - Strict standards, incentives to adopt eco-friendly solutions and objective information on all aspects of carpet to benefit the environment and consumers.  
Made with back2back backing which contains a minimum of 70% post industrial recycled content  
Made with solution-dyed fibers a process that reduces significantly water consumption

#### Limitless designabilities

One of the most versatile floor coverings because you get to choose from a wide range of colors and textures  
Easy to mix and match colors and designs for a personalized look

#### Warm, quiet and comfortable

Without a doubt, the most comfortable flooring  
Greatest soundproofing and insulating properties  
Reduces heat loss  
Soft and warm to the touch

#### High performance

High-performing product made to withstand heavy traffic  
Part of our Modulyss product offering, ideal for general commercial applications

#### Easy to install and repair

Easy installation with our 301 Carpet Tiles Adhesive  
Modular floor covering for fast and easy repair when needed

# Frame TQS2

## Carpet Tiles • Modulyss

### Product Specifications

Market Segments	Hospitality, Pro, Workspace
Brand	Modulyss
Collection	Modulyss
Style Name	Frame
Style Number	TQS2
Colors	4
Construction	Tufted Loop
Format	Tile
Fiber Type	100% BCF Solution Dyed Nylon
Abrasion Resistance	Heavy commercial Use
Dye Method	Solution Dyed
Pile Weight	18.58 oz./y <sup>2</sup> (630.0 g/m <sup>2</sup> )
Pile Height	1/8 in (3.0 mm)
Total Height	17/64 in (6.5 mm)
Backing	Back2Back Modified Bitumen
Stitch Count	0 /in (0 /10 cm)
Gauge	1/12 in (2.11 mm)
Density Factor	5663
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70 & C.G.S.B. 4-GP-129
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	GLP 3325
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, Certified A+, GUT-NR
Installation Methods	Quarter Turn, Monolithic, Brick
	<a href="#">Modulyss Carpet Tiles Installation Guide</a>



### Color Names & Numbers

#F592	F592	#F847	F847
#F942	F942	#F983	F983

### Warranties

- [Modulyss Carpet Tiles Warranty Guide](#)
- [Modulyss Carpet Tiles Maintenance Guide](#)

Commercial use	Static Control 15 Years
	Wear Resistance 15 Years
	Edge Ravelling 15 Years
	Delamination Resistance 15 Years
	Dimensional Stability 15 Years
	Anti-Zippering 15 Years
	Stain Resistance 15 Years
	Colorfastness 15 Years
	Manufacturing Defects 15 Years


# Frame TQS2

## Carpet Tiles • Modulyss

### Colors




#F592  
F592



#F847  
F847



#F942  
F942



#F983  
F983

### Packaging information

Units Per Box	20
Boxes Per Pallet	20
Box Weight	48.50 Pounds (21998.21 Grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	119.6
Square Meters Per Pallet	99.99