#### **Benefits**

Safe and healthy

Antimicrobial protective treatment to inhibit the growth of mold and mildew.

Phthalates-Free products meaning that they will not affect your quality of life FloorScore® Certified for compliance with rigorous indoor air quality requirements

E1 Certified meaning that the product meets the European standard for indoor air quality

Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful

substances.

Performant and durable construction Commercial abrasion resistance

BLC Certified  $\ensuremath{\mathfrak{B}}$  - Ensures that the floor covering you're buying surpasses industry quality standards.

Easy maintenance 100% Waterproof

Antimicrobial, anti-mold and anti-fungal

Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Compatible with embedded radiant heating

Glued installation for a permanent and sturdy setup

Loose lay the planks for a fast installation and an easy repair

Can be installed on all floor levels, even on walls

Coordinating moldings available

Notable look Matte finish

Mix and match colors for a bold look

Best-in-class Warranty 30 Days No Questions Asked Replacement

**Quickship** Stock product for faster delivery

Single Bulletin page 1 of 4

# **Product Specifications**

Market Segments Builder, Hospitality, Pro, Residential,

Senior Living, Workspace

BrandOne2FloorSub CategoryLVTCollectionGalleriaStyle NamePergamonStyle Number2414ConstructionLuxury VinylFormatTile

Abrasion Resistance General Commercial Use

 Material
 Virgin PVC

 Width
 12" (304.8 mm)

 Total Thickness
 0.197" (5 mm)

 Wear Layer Thickness
 0.0220" (0.5500 mm)

InterlayerFiberglassBackingLoose Lay

**Edges** 4-Sided Micro Bevel

Locking System None Finish Stone

**Top Surface** UV-Cured Polyurethane

GlossMattePattern Repeat6IIC66STC67DesignTerrazzoFormaldehydeE1

**Length** 24" (609.6 mm)

Certifications Virgin PVC, FloorScore, E1 Certified,

Phthalates-Free, BLC Certification,

QuickShip

Installation Methods Loose Lay, Compatible with embedded

radiant heating, Glued

Luxury Vinyl Installation Guide

(Loose Lay)

Wall Installation Guide - Luxury

Viny



#### Warranties

☑ Luxury Vinyl Warranty Guide

Luxury Vinyl Care & Maintenance Guide

Residential use Manufacturing Defects

Lifetime
Stain Lifetime
Wear Lifetime
No Questions Asked
Replacement 30 days
Petproof Lifetime
Waterproof Lifetime
Fade Lifetime

Commercial use Fade 15 Years

Manufacturing Defects 15

Years

Stain 15 Years Wear 15 Years Petproof Lifetime Waterproof Lifetime



Single Bulletin page 2 of 4

# Packaging information

Units Per Box 12 Boxes Per Pallet 48

**Box Weight** 45.36 Pounds (20574.93 Grams)

Square Meters Per Box2.23Square Meters Per Pallet107.02Square Feet Per Box24Square Feet Per Pallet1152

### Moldings



MultitrimStair NoseCoordinatingCoordinating94" X 0.23" X 1.593"94" X 1.16" X 2"

 $(2350 \; mm \; X \; 5.842 \; mm \; X \; 40.481 \qquad (2350 \; mm \; X \; 25.4 \; mm \; X \; 50.80 \; mm)$ 

mm)



Single Bulletin page 3 of 4

## Accessories



#### 701 Luxury Vinyl Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Non-Porous: 1/16" x 1/32" x 1/32" V-notch Trowel

#### Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71  $m^2$  / 15 L)

#### Non-Porous Coverage

1,000 to 1,200 sq.ft. / 4 U.S. Gallons (93 to 112 m<sup>2</sup> / 15 L)

- **☑** Label 701 Vinyl Flooring Adhesive
- SDS 701 Vinyl Flooring Adhesive
- ☑ Specifications 701 Vinyl Flooring Adhesive



Single Bulletin page 4 of 4